

Page 1/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.02.2024 Version number 23 Revision: 17.02.2024

### 1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name Konudur 250 OM-PL Winterharz - Komponente A

Relevant identified uses of the substance or mixture and

uses advised against No further relevant information available.

· Application of the substance

/ the mixture Synthetic resin

Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department: msds@mc-bauchemie.de

#### 2 Hazards identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

· Label elements

· GHS label elements The product is classified and labelled according to the Globally

Harmonised System (GHS).

· Hazard pictograms

CHOOSE

GHS05

· Signal word Danger

· Hazard-determining

components of labelling:
Hazard statements
Silicic acid, sodium salt
Causes skin irritation.
Causes serious eye damage.

• Precautionary statements Wear protective gloves / eye protection / face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Immediately call a POISON CENTER/doctor. Specific treatment (see on this label).

(Contd. on page 2)



Page 2/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.02.2024 Version number 23 Revision: 17.02.2024

#### Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 1)

Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

· Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

## 3 Composition/information on ingredients

· Chemical characterisation: Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous com	nponents:	
CAS: 1344-09-8	Silicic acid, sodium salt	10-30%
	Eye Dam. 1, H318; Skin Irrit. 2, H315	
CAS: 1344-09-8	Silicic acid, sodium salt	10-30%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Acute Tox. 5, H303; Acute Tox. 5, H313	
CAS: 107-21-1	ethane-1,2-diol	<5%
	STOT RE 2, H373; Acute Tox. 4, H302; Acute Tox. 5, H313	

Additional information For the wording of the listed hazard phrases refer to section 16.

# 4 First aid measures

· Description of first aid measures

After inhalation Supply fresh air.

In case of unconsciousness bring patient into stable side position

for transport.

· After skin contact Instantly wash with water and soap and rinse thoroughly.

Instantly rinse with water.

· After eye contact Seek medical treatment.

Rinse opened eye for several minutes under running water. Then

consult a doctor.

· After swallowing Rinse out mouth and then drink plenty of water.

Seek medical treatment.

#### 5 Firefighting measures

· Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· Special hazards arising from

the substance or mixture No further relevant information available.

(Contd. on page 3)



Page 3/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.02.2024 Version number 23 Revision: 17.02.2024

Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 2)

· Advice for firefighters

Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and

**emergency procedures** Not required.

Environmental precautions: Dilute with much water.

· Methods and material for

containment and cleaning up: Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust). Ensure adequate ventilation.

· Reference to other sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

#### 7 Handling and storage

· Handling

· Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection

against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Information about storage in

one common storage facility: Not required.

· Further information about

storage conditions: None.
Storage class 12

#### 8 Exposure controls/personal protection

· Additional information about

design of technical systems: No further data; see section 7.

· Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 107-21-1 ethane-1,2-diol

TLV (USA) Short-term value: 10\*\* mg/m³, 50\* ppm

Long-term value: 25\* ppm

\*vapor fraction: \*\*inh. fraction, aerosol only, A4

(Contd. on page 4)



Page 4/9

according to 1907/2006/EC, Article 31

Printing date 17.02.2024

Version number 23

Revision: 17.02.2024

#### Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 3) WEEL (USA) IOELV (European Union) Short-term value: 104 mg/m³, 40 ppm Long-term value: 52 mg/m³, 20 ppm Short-term value: 104\*\* mg/m³, 40\*\* ppm WEL (Great Britain) Long-term value: 10\* 52\*\* mg/m3, 20\*\* ppm Sk \*particulate \*\*vapour · DNELs CAS: 1344-09-8 Silicic acid, sodium salt DNEL 0.8 mg/kg bw/Tag (ArL) Oral DNEL 1.59 mg/kg bw/day (ArL) Dermal Inhalative DNEL 5.61 mg/m³ (ArL) CAS: 1344-09-8 Silicic acid, sodium salt DNEL 0.8 mg/kg bw/Tag (ArL) Oral Dermal DNEL 1.59 mg/kg bw/day (ArL) Inhalative DNEL 5.61 mg/m³ (ArL) CAS: 107-21-1 ethane-1,2-diol DNEL 106 mg/kg bw/day (ArL) Dermal Inhalative DNEL 35 mg/m³ (ArL) · PNECs CAS: 1344-09-8 Silicic acid, sodium salt PNEC 348 mg/l (Kla) 1 mg/l (Mew) 7.5 mg/l (Freshwater) CAS: 1344-09-8 Silicic acid, sodium salt PNEC 348 mg/l (Kla) 1 mg/l (Mew) 7.5 mg/l (Freshwater)

· Additional information:

The lists that were valid during the compilation were used as basis.

- · Exposure controls
- · Personal protective equipment
- · General protective and

hygienic measures Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

• Breathing equipment: In case of brief exposure or low pollution or when application is

performed at confined area with adequate mechanical ventilation meeting local authority requirements, use breathing filter apparatus. In case of intensive or longer exposure use breathing

apparatus that is independent of circulating air.

(Contd. on page 5)



Page 5/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.02.2024 Version number 23 Revision: 17.02.2024

#### Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 4)

· **Protection of hands:** Protective gloves.

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

application.

· Penetration time of glove

material

The exact breakthrough time must be obtained from the protective

glove manufacturer and must be observed.

Eye protection: Tightly sealed safety glasses.Body protection: Protective work clothing.

## 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid Colour: Whitish

· Smell: Weak, characteristic

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Not determined

Initial boiling point and boiling range: 100 °C

· Flash point: Not applicable

· **Self-inflammability:** Product is not selfigniting.

• Explosive properties: Product is not explosive.

· Steam pressure at 20 °C: 23 hPa

Density Not determined

· Solubility in / Miscibility with

Water: Fully miscible

· Viscosity:

dynamic: Not determined. kinematic: Not determined.

(Contd. on page 6)



Page 6/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.02.2024 Version number 23 Revision: 17.02.2024

#### Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 5)

· Other information

No further relevant information available.

# 10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

Thermal decomposition /

**conditions to be avoided:** No decomposition if used according to specifications.

· Possibility of hazardous

reactions

No dangerous reactions known

· Conditions to avoid · Incompatible materials:

No further relevant information available. No further relevant information available.

· Hazardous decomposition

products:

No dangerous decomposition products known

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

LD/LC50 values that are relevant for classification:

# Oral LD50 3400 mg/kg (rat) Dermal LD50 4640 mg/kg (rabbit)

>5000 mg/kg (rat)

## CAS: 1344-09-8 Silicic acid, sodium salt

Oral	LD50	3400 mg/kg (rat)
Dermal	LD50	4640 mg/kg (rabbit)
		>5000 mg/kg (rat)

# CAS: 107-21-1 ethane-1,2-diol

Oral LD50 4000 mg/kg (rat)	
----------------------------	--

LDL0 1600 mg/kg (Workers)

Dermal LD50 >3500 mg/kg (mouse) 10600 mg/kg (rabbit)

· Primary irritant effect:

· **Skin corrosion/irritation** Irritant for skin and mucous membranes.

· Serious eye damage/irritation Strong irritant with the danger of severe eye injury.

· Respiratory or skin

**sensitisation** No sensitizing effect known.

(Contd. on page 7)



Page 7/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.02.2024 Version number 23 Revision: 17.02.2024

#### Trade name Konudur 250 OM-PL Winterharz - Komponente A

· Additional toxicological information:

(Contd. of page 6)

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

# 12 Ecological information

· Toxicity

· Aquatic toxicity:

CAS: 1344-09-8 Silicic acid, sodium salt

EC50/72h | >345.4 mg/l (Desmodesmus subspicatus)

LC50/96h 1108 mg/l (Danio rerio)

260 mg/l (Oncorhynchus mykiss)

>100 mg/l (fish)

EC50 >100 mg/l (Bak)

>100 mg/l (algae) >100 mg/l (Daphnien)

>100 mg/l (Daphnia magna)

EC50/48h | 1700 mg/l (Daphnia magna)

CAS: 1344-09-8 Silicic acid, sodium salt

EC50/72h >345.4 mg/l (Desmodesmus subspicatus)

LC50/96h 1108 mg/l (Danio rerio)

260 mg/l (Oncorhynchus mykiss)

>100 mg/l (fish)

EC50 >100 mg/l (Bak)

>100 mg/l (algae)

>100 mg/l (Daphnien)

>100 mg/l (Daphnia magna)

EC50/48h | 1700 mg/l (Daphnia magna)

CAS: 107-21-1 ethane-1,2-diol

LC50/96h | 72860 mg/l (Pimephales promelas)

EC50/48h >100 mg/l (Daphnia magna)

EC50/96h | 6500-13000 mg/l (Selenastrum capricornutum)

NOEC 8590 mg/l (Ceriodaphnia dubia)

15380 mg/l (Pimephales promelas)

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 8)



Page 8/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.02.2024 Version number 23 Revision: 17.02.2024

#### Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 7)

· Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

Other adverse effects No further relevant information available.

# 13 Disposal considerations

· Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

· Recommended cleaning

agent: Water, if necessary with cleaning agent.

UN-Number		
ADR, ADN, IMDG, IATA	Void	
UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
Packing group		
ADR, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
UN "Model Regulation":	Void	

AE



Page 9/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.02.2024 Version number 23 Revision: 17.02.2024

Trade name Konudur 250 OM-PL Winterharz - Komponente A

(Contd. of page 8)

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous

substances - ANNEX I None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data

specification sheet: Environment protection department.

· Contact:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 5: Acute toxicity – Category 5 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· \* Data compared to the previous version altered.