



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.02.2022

Version number 16

Revision: 15.02.2022

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name** MC-CarboSolid 1209 TX - Komponente B
- **Relevant identified uses of the substance or mixture and uses advised against** *No further relevant information available.*
- **Application of the substance / the mixture** *Epoxy coating*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** *MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de*

*MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533*
- **Informing department:** *msds@mc-bauchemie.de*
- **Emergency telephone number:** *Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565*

2 Hazards identification

- **Classification of the substance or mixture**
 - Flam. Liq. 4 H227 Combustible liquid.*
 - Acute Tox. 4 H302 Harmful if swallowed.*
 - Acute Tox. 5 H313 May be harmful in contact with skin.*
 - Acute Tox. 5 H333 May be harmful if inhaled.*
 - Skin Corr. 1A H314 Causes severe skin burns and eye damage.*
 - Eye Dam. 1 H318 Causes serious eye damage.*
 - Skin Sens. 1 H317 May cause an allergic skin reaction.*
 - Aquatic Acute 3 H402 Harmful to aquatic life.*
 - Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.*
- **Label elements**
- **GHS label elements** *The product is classified and labelled according to the Globally Harmonised System (GHS).*
- **Hazard pictograms**



GHS05 GHS07

(Contd. on page 2)

AE



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.02.2022

Version number 16

Revision: 15.02.2022

Trade name MC-CarboSolid 1209 TX - Komponente B

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:** 2-methylpentane-1,5-diamine
3-aminomethyl-3,5,5-trimethylcyclohexylamine
Benzyl alcohol
Amine polymer
- **Hazard statements** Combustible liquid.
Harmful if swallowed.
May be harmful in contact with skin.
May be harmful if inhaled.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.
- **Precautionary statements** Do not breathe dusts or mists.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

471-34-1	calcium carbonate Acute Tox. 5, H303	25-50%
9046-10-0	Polyoxypropylenediamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 5, H303; Acute Tox. 5, H313; Aquatic Chronic 3, H412	≥5-<25%
	Amine polymer Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	≥10-<25%
15520-10-2	2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Flam. Liq. 4, H227	≥5-<25%
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥5-<10%

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.02.2022

Version number 16

Revision: 15.02.2022

Trade name MC-CarboSolid 1209 TX - Komponente B

(Contd. of page 2)

1761-71-3	4,4'-methylenebis(cyclohexylamine) Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 5, H313; Aquatic Acute 2, H401	≥5-<10%
	Amine polymer Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	≥3-<10%
100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	<5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **After inhalation** Supply fresh air.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Seek medical treatment.
- **After swallowing** Rinse out mouth and then drink plenty of water. Seek medical treatment.
- **Information for doctor**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:** Collect mechanically.
- **Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.

(Contd. on page 4)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.02.2022

Version number 16

Revision: 15.02.2022

Trade name MC-CarboSolid 1209 TX - Komponente B

(Contd. of page 3)

See Section 13 for information on disposal.

7 Handling and storage

- **Handling**
- **Precautions for safe handling** Store in cool, dry place in tightly closed containers. Open and handle container with care.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

100-51-6 Benzyl alcohol

WEEL (USA) Long-term value: 10 ppm

· **DNELs**

471-34-1 calcium carbonate

Inhalative DNEL 4.26 mg/m³ (ArL)

9046-10-0 Polyoxypropylenediamine

Oral DNEL 0.04 mg/kg bw/Tag (ArL)

Dermal DNEL 2.5 mg/kg bw/day (ArL)

15520-10-2 2-methylpentane-1,5-diamine

Dermal DNEL 1.5 mg/kg bw/day (ArL)

Inhalative DNEL 0.25 mg/m³ (ArL)

0.5 mg/m³ (Ark)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral DNEL 0.526 mg/kg bw/Tag (ArL)

Inhalative DNEL 20.1 mg/m³ (ArL)

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.02.2022

Version number 16

Revision: 15.02.2022

Trade name MC-CarboSolid 1209 TX - Komponente B

(Contd. of page 4)

1761-71-3 4,4'-methylenebis(cyclohexylamine)

Oral	DNEL	0.06 mg/kg bw/Tag (ArL)
Dermal	DNEL	0.1 mg/kg bw/day (ArL)
Inhalative	DNEL	1 mg/m ³ (ArL)

100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL)
		20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL)
		40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL)
		110 mg/m ³ (Ark)

· PNECs

9046-10-0 Polyoxypropylenediamine

PNEC	7.5 mg/l (Sewage Treatment Plant)
	0.015 mg/l (Fresh water)
PNEC	0.0176 mg/kg dwt (Bod)
	0.125 mg/kg dwt (Sediment)
	0.132 mg/kg dwt (Fresh water sediment)

15520-10-2 2-methylpentane-1,5-diamine

PNEC	0.042 mg/l (Mew)
	0.42 mg/l (Suw)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

PNEC	0.006 mg/l (Mew)
	0.06 mg/l (Suw)
PNEC	0.578 mg/kg dwt (Sediment)
	5.784 mg/kg dwt (Fresh water sediment)

1761-71-3 4,4'-methylenebis(cyclohexylamine)

PNEC	0.08 mg/l (Fresh water)
	3.2 mg/l (Kla)
	13.7 mg/l (Mew)
PNEC	27.2 mg/kg dwt (Bod)
	13.7 mg/kg dwt (Sediment)
	137 mg/kg dwt (Fresh water sediment)

100-51-6 Benzyl alcohol

PNEC	0.527 mg/l (Marine water sediment)
	0.1 mg/l (Mew)
	1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod)
	5.27 mg/kg dwt (Fresh water sediment)

(Contd. on page 6)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.02.2022

Version number 16

Revision: 15.02.2022

Trade name MC-CarboSolid 1209 TX - Komponente B

(Contd. of page 5)

- **Additional information:** *The lists that were valid during the compilation were used as basis.*
- **Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures** *Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.*
- **Protection of hands:** *Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.*
- **Material of gloves** *The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*
- **Penetration time of glove material** *The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.*
- **Eye protection:** *Safety glasses
Tightly sealed safety glasses.*
- **Body protection:** *Protective work clothing.*

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

- **Form:** *Pasty*
- **Colour:** *Black*
- **Smell:** *Amine-like*

· **pH-value at 20 °C:** *12*

· Change in condition

- **Melting point/freezing point:** *Not determined*
- **Initial boiling point and boiling range:** *193 °C*

· **Flash point:** *≥61 °C*

· **Ignition temperature:** *380 °C*

· **Self-inflammability:** *Product is not selfigniting.*

· **Explosive properties:** *Product is not explosive.*

· **Density at 20 °C** *1.28 g/cm³*

· **Solubility in / Miscibility with Water:** *Partly miscible*

(Contd. on page 7)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.02.2022

Version number 16

Revision: 15.02.2022

Trade name MC-CarboSolid 1209 TX - Komponente B

(Contd. of page 6)

- **Viscosity:**
dynamic at 20 °C: 40000 mPas
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values that are relevant for classification:**

471-34-1 calcium carbonate

Oral	LD50	>2000 mg/kg (rat)
------	------	-------------------

9046-10-0 Polyoxypropylenediamine

Oral	LD50	2855 mg/kg (Rat)
------	------	------------------

Dermal	LD50	2980 mg/kg (Kan)
--------	------	------------------

15520-10-2 2-methylpentane-1,5-diamine

Oral	LD50	1170 mg/kg (rat)
------	------	------------------

Dermal	LD50	1870 mg/kg (rabbit)
--------	------	---------------------

Inhalative	LC50/4 h	19.6 mg/l (rat)
------------	----------	-----------------

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	LD50	1030 mg/kg (rat)
------	------	------------------

	NOAEL	250 mg/kg (rat)
--	-------	-----------------

Dermal	LD50	1840 mg/kg (rabbit)
--------	------	---------------------

		>2000 mg/kg (rat)
--	--	-------------------

1761-71-3 4,4'-methylenebis(cyclohexylamine)

Oral	LD50	380 mg/kg (rat)
------	------	-----------------

Dermal	LD50	2110 mg/kg (rat)
--------	------	------------------

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.02.2022

Version number 16

Revision: 15.02.2022

Trade name MC-CarboSolid 1209 TX - Komponente B

(Contd. of page 7)

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

· **Primary irritant effect:**

· **Skin corrosion/irritation** Caustic effect on skin and mucous membranes.

· **Serious eye damage/irritation** Strong caustic effect.

· **Respiratory or skin sensitisation** Sensitization possible by skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

471-34-1 calcium carbonate

IC50/72h	>1000 mg/l (algae)
LC50/24h	>10 mg/l (fish)
LC50/96h	>1000 mg/l (fish)
EC50/48h	>1000 mg/l (Daphnia magna)

15520-10-2 2-methylpentane-1,5-diamine

EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (Daphnia magna)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

LC50/96h	110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodesmus subspicatus) 3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodesmus subspicatus)

1761-71-3 4,4'-methylenebis(cyclohexylamine)

LC50/96h	>100 mg/l (Leucidus idus)
EC50/48h	6.84 mg/l (Daphnia magna)
NOEC	4 mg/l (Daphnia magna)

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.02.2022

Version number 16

Revision: 15.02.2022

Trade name MC-CarboSolid 1209 TX - Komponente B

(Contd. of page 8)

ErC50/72h 141.2 mg/l (*Desmodemus subspicatus*)

100-51-6 Benzyl alcohol

IC50/72h 700 mg/l (algae)

LC50/96h 460 mg/l (*Pimephales promelas*)

10 mg/l (*Lepomis macrochirus*)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Danger to drinking water if even extremely small quantities leak into soil.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14 Transport information

- **UN-Number**
- **ADR, IMDG, IATA** UN2735
- **UN proper shipping name**
- **ADR, IMDG, IATA** AMINES, LIQUID, CORROSIVE, N.O.S. (2-methylpentane-1,5-diamine, 4,4'-methylenebis(cyclohexylamine))
- **Transport hazard class(es)**
- **ADR**
- **Class** 8 (C7) Corrosive substances.
- **Label** 8
- **IMDG, IATA**
- **Class** 8 Corrosive substances.
- **Label** 8

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.02.2022

Version number 16

Revision: 15.02.2022

Trade name MC-CarboSolid 1209 TX - Komponente B

(Contd. of page 9)

· Packing group · ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Kemler Number: · EMS Number: · Segregation groups · Stowage Category · Segregation Code	Warning: Corrosive substances. 88 F-A,S-B Alkalis A SG35 Stow "separated from" SGG1-acids
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	0 Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	1 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	0 Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (2-METHYLPENTANE-1, 5-DIAMINE, 4, 4'-METHYLENEBIS(CYCLOHEXYLAMINE)), 8, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing data specification sheet:** Environment protection department.

(Contd. on page 11)



BE SURE. BUILD SURE.

Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.02.2022

Version number 16

Revision: 15.02.2022

Trade name MC-CarboSolid 1209 TX - Komponente B

(Contd. of page 10)

· **Contact:**

- **Abbreviations and acronyms:** RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 5: Acute toxicity – Category 5
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- * **Data compared to the previous version altered.**

AE