

Page 1/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 31 Revision: 09.03.2024

### 1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name MC-DUR 1177 WV-A - Komponente B

Relevant identified uses of the substance or mixture and

**uses advised against** No further relevant information available.

· Application of the substance

/ the mixture Epoxy impregnation

EP-Additives Hardening agent/ Curing agent

· Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department: msds@mc-bauchemie.de

## 2 Hazards identification

· Classification of the substance or mixture

Eye Dam. 1 H318 Causes serious eye damage. Skin Sens. 1 H317 May cause an allergic skin reaction.

· Label elements

· GHS label elements The product is classified and labelled according to the Globally

Harmonised System (GHS).

· Hazard pictograms

GHS05 GHS07

· **Signal word** Danger

Hazard-determining

components of labelling: Polymer Epoxidharz-Addukt

Aminpolymer

Hazard statements Causes serious eye damage.

May cause an allergic skin reaction.

• Precautionary statements Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 2)



Page 2/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 31 Revision: 09.03.2024

#### Trade name MC-DUR 1177 WV-A - Komponente B

(Contd. of page 1)

Wear protective gloves / eye protection / face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

· Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### 3 Composition/information on ingredients

· Chemical characterisation: Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:		
CAS: 260549-92-6	Polymer Epoxidharz-Addukt	30-60%
	Eye Dam. 1, H318	
CAS: 180583-06-6	Aminpolymer	10-30%
	Skin Sens. 1, H317	
CAS: 112-57-2	3,6,9-triazaundecamethylenediamine	≥0.25-<0.5%
	Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	

· Additional information For the wording of the listed hazard phrases refer to section 16.

# 4 First aid measures

· Description of first aid measures

· General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

• After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

· After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

· After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

(Contd. on page 3)



Page 3/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 31 Revision: 09.03.2024

#### Trade name MC-DUR 1177 WV-A - Komponente B

(Contd. of page 2)

 Information for doctor
 Most important symptoms and effects, both acute and

and effects, both acute a delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

## 5 Firefighting measures

· Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· Special hazards arising from

the substance or mixture

No further relevant information available.

· Advice for firefighters

• Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and

emergency procedures Not required.

Environmental precautions: Prevent material from reaching sewage system, holes and cellars.

Dilute with much water.

· Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

· Reference to other sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

#### 7 Handling and storage

· Handling

· Precautions for safe handling Open and handle containers with care.

Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required.

are required.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins. Open and handle containers with care.

(Contd. on page 4)



Page 4/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 31 Revision: 09.03.2024

#### Trade name MC-DUR 1177 WV-A - Komponente B

(Contd. of page 3)

· Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working

areas. Take precautionary measures to avoid electrostatic

discharges.

· Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

**storage conditions:** Protect from heat and direct sunlight.

Storage class 12

## 8 Exposure controls/personal protection

· Additional information about

design of technical systems: No further data; see section 7.

· Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

WEEL (USA) Long-term value: 5 mg/m³

Skin; DSEN

#### · DNELs

#### CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

Oral DNEL 0.53 mg/kg bw/Tag (ArL)
Dermal DNEL 0.74 mg/kg bw/day (ArL)
Inhalative DNEL 6940 mg/m³ (ArL)

#### · PNECs

#### CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

PNEC 9.73 mg/l (BEL)

0.0068 mg/l (Fresh water)

0.0068 mg/l (Mew)

PNEC 0.343 mg/kg dwt (Sediment)

3.43 mg/kg dwt (Fresh water sediment)

• Additional information: The lists that were valid during the compilation were used as basis.

· Exposure controls

· Personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

· Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/

(Contd. on page 5)



Page 5/9

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 09.03.2024 Printing date 09.03.2024 Version number 31

#### Trade name MC-DUR 1177 WV-A - Komponente B

(Contd. of page 4)

white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

· Protection of hands: Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

· Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be

checked before use. Nitrile rubber

Recommended material thickness:≥ 0.4 mm

Penetration time of glove material

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

· Eye protection: Safety goggles.

Protective clothing · Body protection:

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.

(Contd. on page 6)



Page 6/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 09.03.2024 Printing date 09.03.2024 Version number 31

Not determined.

Trade name MC-DUR 1177 WV-A - Komponente B

(Contd. of page 5)

### 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid Colour: Transparent · Smell: Characteristic · pH-value:

· Change in condition

Melting point/freezing point: <0 °C Initial boiling point and boiling range: 100 °C

· Flash point: Not applicable

· Self-inflammability: Product is not selfigniting.

· Explosive properties: Product is not explosive.

23 hPa · Steam pressure at 20 °C:

· Density at 20 °C 1.07 g/cm<sup>3</sup>

· Solubility in / Miscibility with

Water: Fully miscible

· Viscosity:

dynamic: Not determined. kinematic: Not determined.

· Other information

No further relevant information available.

# 10 Stability and reactivity

Reactivity No further relevant information available.

· Chemical stability

Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous

reactions

No dangerous reactions known

· Conditions to avoid No further relevant information available. · Incompatible materials: No further relevant information available.

· Hazardous decomposition

products:

No dangerous decomposition products known



Page 7/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 31 Revision: 09.03.2024

Trade name MC-DUR 1177 WV-A - Komponente B

(Contd. of page 6)

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 values that are relevant for classification:

CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

Oral LD50 2140 mg/kg (rat)
Dermal LD50 1260 mg/kg (rabbit)

Primary irritant effect:

· Serious eye damage/irritation Strong irritant with the danger of severe eye injury.

· Respiratory or skin

sensitisation Sensitization possible by skin contact.

· Additional toxicological

information: The product shows the following dangers according to the

calculation method of the General EC Classification Guidelines for

Preparations as issued in the latest version:

Irritant

### 12 Ecological information

· Toxicity

#### · Aquatic toxicity:

CAS: 112-57-2 3,6,9-triazaundecamethylenediamine

EC50/72h | 2.1 mg/l (algae) LC50/96h | 420 mg/l (Gup)

EC50/48h 24.1 mg/l (Daphnia magna)

- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:

Bioaccumulative potential
 Mobility in soil
 No further relevant information available.
 No further relevant information available.

Additional ecological information:

• General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

• Other adverse effects No further relevant information available.

AF

(Contd. on page 8)



Page 8/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 31 Revision: 09.03.2024

Trade name MC-DUR 1177 WV-A - Komponente B

(Contd. of page 7)

### 13 Disposal considerations

· Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

· Recommended cleaning

agent: Water, if necessary with cleaning agent.

# **14 Transport information**

14 Transport information		
· UN-Number · ADR, ADN, IMDG, IATA	Void	
· UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· Packing group · ADR, IMDG, IATA	Void	
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
· Transport in bulk according to Anne Marpol and the IBC Code	ex II of Not applicable.	
· UN "Model Regulation":	Void	

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous

**substances - ANNEX I** None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

AΕ



Page 9/9

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 09.03.2024 Version number 31 Revision: 09.03.2024

Trade name MC-DUR 1177 WV-A - Komponente B

(Contd. of page 8)

## 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data

specification sheet: Environment protection department.

· Contact:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par

route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

\* \* Data compared to the previous version altered.