

Page 1/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

*

*

Version number 26

Revision: 01.03.2024

Product identifier	
Trade name Relevant identified uses of	MC-DUR 2500 - Komponente A
the substance or mixture and uses advised against Application of the substance	No further relevant information available.
/ the mixture	Polyurethane lacquer
Details of the supplier of the s	safety data sheet MC-Bauchemie Müller GmbH & Co. KG
Manufacturer/Supplier:	Am Kruppwald 1-8
	D-46238 Bottrop
	Tel.: +49(0)2041-101-0
	Fax.: +49(0)2041-101-400
	E-Mail: info@mc-bauchemie.de
	MC-Bauchemie AG
	Hagackerstr. 10
	CH-8953 Dietikon
	Tel.: +44-7400510 Fax : +44-7400533
Informing department:	msds@mc-bauchemie.de
monning department.	msus@me-bauenemie.ue
Hazards identification	
Classification of the substanc	
Classification of the substand Skin Corr. 3	H316 Causes mild skin irritation.
Classification of the substand Skin Corr. 3 Serious eye damage/irritation –	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation.
Classification of the substanc Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation.
Classification of the substand Skin Corr. 3 Serious eye damage/irritation –	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects The product is classified and labelled according to the Globa
Classification of the substance Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3 Label elements	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects
Classification of the substance Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3 Label elements GHS label elements	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects The product is classified and labelled according to the Globa
Classification of the substance Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3 Label elements GHS label elements	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects The product is classified and labelled according to the Globa
Classification of the substance Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3 Label elements GHS label elements	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects The product is classified and labelled according to the Globa
Classification of the substance Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3 Label elements GHS label elements	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects The product is classified and labelled according to the Globa Harmonised System (GHS).
Classification of the substance Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3 Label elements GHS label elements Hazard pictograms	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects The product is classified and labelled according to the Globa Harmonised System (GHS). GHS07 Warning Causes mild skin irritation.
Classification of the substance Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3 Label elements GHS label elements Hazard pictograms Signal word	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects The product is classified and labelled according to the Globa Harmonised System (GHS). GHS07 Warning Causes mild skin irritation. Causes serious eye irritation.
Classification of the substance Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3 Label elements GHS label elements Hazard pictograms Signal word Hazard statements	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects The product is classified and labelled according to the Globa Harmonised System (GHS). GHS07 Warning Causes mild skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.
Classification of the substance Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3 Label elements GHS label elements Hazard pictograms Signal word	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects The product is classified and labelled according to the Globa Harmonised System (GHS). GHS07 Warning Causes mild skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. Avoid release to the environment.
Classification of the substance Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3 Label elements GHS label elements Hazard pictograms Signal word Hazard statements	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects The product is classified and labelled according to the Globa Harmonised System (GHS).
Classification of the substance Skin Corr. 3 Serious eye damage/irritation – Aquatic Chronic 3 Label elements GHS label elements Hazard pictograms Signal word Hazard statements	H316 Causes mild skin irritation. Category 2A H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects The product is classified and labelled according to the Globe Harmonised System (GHS). GHS07 Warning Causes mild skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. Avoid release to the environment. Wear eye protection / face protection. IF IN EYES: Rinse cautiously with water for several minute



Printing date 01.03.2024

Version number 26

Revision: 01.03.2024

Trade name MC-DUR 2500 - Komponente A

(Contd. of page 1)

Page 2/9

If eye irritation persists: Get medical advice/attention. Dispose of contents/container in accordance with local/regional/ national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: · vPvB:

Not applicable. Not applicable.

- 3 Composition/information on ingredients
- · Identification number(s): void
- Chemical characterisation: Mixtures

indian affinad aid maaaanna

• **Description:** Mixture consisting of the following components.

[.] Dangerous comp	oonents:	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	<i>≥</i> 2.5-<3%
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	
CAS: 78330-21-9	Fatty alcohol polyglycol ether	≥1-<1.5%
	Eye Dam. 1, H318; Aquatic Chronic 3, H412	
CAS: 8000-41-7	Terpineol	<1.5%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319	

4 First aid measures

 Description of first aid meas General information 	Remove, decontaminate and dispose of soiled, soaked clothing
General mormation	and shoes immediately.
· After inhalation	Remove person to fresh air, keep warm, allow to rest; if breathing
Alter minalation	
After alin ac the st	is difficult, seek medical attention.
· After skin contact	In case of contact with skin, preferably wash with polyethylene
	glycol-based cleaner or clean with plenty of warm water and soap.
	Consult a doctor in case of skin reactions.
· After eye contact	Rinse the eyes with open eyelids for a sufficiently long time (at
	least 10 minutes) with water that is as lukewarm as possible.
	Consult an ophthalmologist.
· After swallowing	Do NOT induce vomiting. Rinse mouth with water. Medical attention required.
 Information for doctor 	
 Most important symptoms 	
and effects, both acute and	
delayed	Information for the doctor: The product irritates the respiratory tract and is a potential trigger for skin and respiratory sensitisation.
	Treatment of acute irritation or bronchial constriction is primarily
	symptomatic. Depending on the extent of exposure and the
	symptoms, prolonged medical treatment may be necessary.
	(Contd. on page 3)



Page 3/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 26

Revision: 01.03.2024

Trade name MC-DUR 2500 - Komponente A

· Indication of any immediate medical attention and special treatment needed No information available. (Contd. of page 2)

5 Firefighting measures

· Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment. CO2, extinguishing powder or water jet. Fight larger fire with alcohol-resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available. · Advice for firefighters · Protective equipment:
 - No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective clothing. • Environmental precautions: No special measures required. · Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Reference to other sections No dangerous materials are released.

7 Handling and storage

·Handling

· Precautions for safe handling Ensure sufficient air exchange and/or extraction in the work areas. Air extraction is required for spray application.

For solid products: Avoid dust formation and dust deposits.

Air limit values mentioned in section 8 must be monitored.

At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.

For products containing solvents: Explosion protection required. The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.

Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.

(Contd. on page 4)

AE



Page 4/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 26

Revision: 01.03.2024

Trade name MC-DUR 2500 - Komponente A

	(Contd. of page 3
 Conditions for safe storage, 	
including any	
incompatibilities	Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.
[.] Storage	
Requirements to be met by	
storerooms and containers:	Store only in the original container.
• Further information about	
storage conditions:	None. 10
 Storage class Specific end use(s) 	No further relevant information available.
Specific end use(s)	
9 Expedure controlo/poroc	nal protoction
8 Exposure controls/perso	mar protection
Additional information about	
design of technical systems:	No further data; see section /.
 Control parameters 	
Components with critical	
values that require	—
monitoring at the workplace:	The product does not contain any relevant quantities of materials
· Additional information:	with critical values that have to be monitored at the workplace. The lists that were valid during the compilation were used as basis.
	The lists that were valid during the compliation were used as basis.
Exposure controls	1
 Personal protective equipmen General protective and 	11
hygienic measures	Keep away from food, drink and animal feed.
nygieme measures	Remove soiled, soaked clothing immediately.
	Wash hands before breaks and at the end of work.
	Avoid contact with eyes and skin.
· Breathing equipment:	Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks o combination filters A2-P2 (EN529) are recommended for short
	term work.
	If applicable, further recommendations for respiratory protection
	can be found in the appendix.
	In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.
· Protection of hands:	Suitable materials for protective gloves; EN 374:
, receipin or nanda.	Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).
	Note: suitable materials that provide sufficient protection fo
	industrial cleaning with aprotic polar solvents (according to IUPAC
	definition): butyl rubber.
	In case of prolonged or frequently repeated contact, a glove with a
	protection class of 5 or higher is recommended (breakthrough time
	protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN374). For short-tern
	protection class of 5 or higher is recommended (breakthrough time



Printing date 01.03.2024

Version number 26

Revision: 01.03.2024

Page 5/9

Trade name MC-DUR 2500 - Komponente A

	(Contd. of page 4)
	according to EN374).
	The thickness of the material is not the only criterion for the level of protection of a glove against a chemical substance. The protective effect also depends to a large extent on the type of glove material. Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multi- layer gloves, which guarantee sufficient protection even with a thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide sufficient protection for short periods of wear. For solvent-free products:
	Example: Polychloroprene - CR: thickness ≥0.5mm; breakthrough time ≥480min.
	Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: thickness ≥0.4mm; breakthrough time ≥480min.
	Recommendation: Dispose of contaminated gloves.
 Material of gloves 	Polychloroprene - CR
	Nitrile rubber - NBR
	Butyl rubber - IIR Fluoro rubber - FKM
· Penetration time of glove	
material	Polychloroprene - CR: thickness ≥0.5mm; breakthrough time ≥480min.
	Nitrile rubber - NBR: thickness ≥0.35mm; breakthrough time ≥480min.
	Butyl rubber - IIR: thickness ≥0.5mm; breakthrough time ≥480min. Fluoro rubber - FKM: Thickness ≥0.4mm; Breakthrough time ≥480min.
• Eye protection:	Safety goggles with side protection in accordance with EN 166.
Body protection:	Use chemical-resistant protective clothing.
	In case of hypersensitivity of the skin, handling the product is not recommended.

Information on basic phy General Information	sical and chemical properties	
Appearance:		
Form:	Liquid	
Colour:	Whitish	
Smell:	Light	
		(Contd. on page



Printing date 01.03.2024

Version number 26

Revision: 01.03.2024

Page 6/9

Trade name MC-DUR 2500 - Komponente A

pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Not determined	
Initial boiling point and boiling ra	nge: 100 °C	
Flash point:	224 °C	
Self-inflammability:	Product is not selfigniting.	
Explosive properties:	Product is not explosive.	
Steam pressure at 20 °C:	23 hPa	
Density at 20 °C	1 g/cm³	
Solubility in / Miscibility with		
Water:	Emulsifiable	
Viscosity:		
dynamic:	Not determined.	
kinematic:	Not determined.	
Other information		

No further relevant information available.

10 Stability and reactivity

conditions to be avoided:

· Possibility of hazardous

· Reactivity

reactions

No further relevant information available.

· Chemical stability · Thermal decomposition /

· Conditions to avoid

No decomposition if used according to specifications.

No dangerous reactions known No further relevant information available. No further relevant information available.

Incompatible materials: No

 Hazardous decomposition products:

No dangerous decomposition products known

11 Toxicological information • Information on toxicological effects • Acute toxicity • LD/LC50 values that are relevant for classification: CAS: 78330-21-9 Fatty alcohol polyglycol ether Oral LD50 Dermal LD50 >2000 mg/kg (rat) (Contd. on page 7)



Page 7/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 01.03.2024

Version number 26

Revision: 01.03.2024

(Contd. of page 6)

Trade name MC-DUR 2500 - Komponente A

- · Primary irritant effect:
- · Serious eye damage/irritation No irritant effect.
- · Respiratory or skin

sensitisation

No sensitizing effect known.

· Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version: When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

12 Ecological information

· Toxicity

· Aquatic toxicity:

LC50/96h 1-10 mg/l (Danio rerio)

EC50 >1000 mg/l (Bak)

EC50/48h 5-10 mg/l (Daphnia magna)

· Persistence and degradability No further relevant information available.

- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- Do not allow undiluted product or large quantities of it to reach · General notes: ground water, water bodies or sewage system.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

 Waste treatment methods Recommendation 	Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 Uncleaned packagings: Recommendation: 	Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

(Contd. on page 8)



Printing date 01.03.2024

Version number 26

Revision: 01.03.2024

Trade name MC-DUR 2500 - Komponente A

(Contd. of page 7)

Page 8/9

UN-Number	
ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	
ADR, ADN, IMDG, IATA	Void
Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	Void
Packing group	
ADR, IMDG, IATA	Void
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex	ll of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications
UN "Model Regulation":	Void

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous
- substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

 Department issuing data specification sheet: Contact: 	Environment protection department.
• Abbreviations and acronyms:	RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods
	(Contd. on page 0)



Printing date 01.03.2024

Version number 26

Revision: 01.03.2024

Page 9/9

Trade name MC-DUR 2500 - Komponente A

	(Contd. of page 8
	IATA: International Air Transport Association
	EINECS: European Inventory of Existing Commercial Chemical Substances
	ELINCS: European List of Notified Chemical Substances
	CAS: Chemical Abstracts Service (division of the American Chemical Society)
	LC50: Lethal concentration, 50 percent
	LD50: Lethal dose, 50 percent
	PBT: Persistent, Bioaccumulative and Toxic
	vPvB: very Persistent and very Bioaccumulative
	Flam. Liq. 3: Flammable liquids – Category 3
	Skin Irrit. 2: Skin corrosion/irritation – Category 2
	Skin Corr. 3: Skin corrosion/irritation – Category 3
	Eye Dam. 1: Serious eye damage/eye irritation – Category 1
	Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
	Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation Category 2A
	STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1
	Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquati hazard – Category 2
	Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquati hazard – Category 3
· * Data compared to the	
previous version altered.	