

Page 1/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021 Version number 6 Revision: 17.10.2021

### 1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

• Trade name MC-Estrifan IH - Komponente B

Relevant identified uses of the substance or mixture and

**uses advised against** No further relevant information available.

Application of the substance

/ the mixture Epoxy resin Injektion

Hardening agent/ Curing agent

· Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department:

Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +48612864565

msds@mc-bauchemie.de

### 2 Hazards identification

· Classification of the substance or mixture

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 5 H313 May be harmful in contact with skin.

Acute Tox. 5 H333 May be harmful if inhaled.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements

• GHS label elements The product is classified and labelled according to the Globally

Harmonised System (GHS).

· Hazard pictograms



GHS05 GHS07

(Contd. on page 2)



Page 2/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021 Version number 6 Revision: 17.10.2021

#### Trade name MC-Estrifan IH - Komponente B

(Contd. of page 1)

· Signal word

· Hazard-determining

components of labelling: 2-methylpentane-1,5-diamine

Danger

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Benzyl alcohol Amine polymer

· Hazard statements Harmful if swallowed.

May be harmful in contact with skin.

May be harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· Chemical characterisation: Mixtures

• **Description:** Binding agent with colouring agents.

Mixture consisting of the following components.

· Dangerous	components:	
15520-10-2	2-methylpentane-1,5-diamine	25-50%
	Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Flam. Liq. 4, H227	_
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	25-50%
	Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	_
	Amine polymer	≥10-<25%
	Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	_
100-51-6	Benzyl alcohol	<25%
	Acute Tox. 4, H302; Acute Tox. 4, H332	-
9046-10-0	Polyoxypropylenediamine	≥5-<10%
	Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 5, H303; Acute Tox. 5, H313; Aquatic Chronic 3, H412	_
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	<1.5%
	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	-

(Contd. on page 3)



Page 3/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021 Version number 6 Revision: 17.10.2021

Trade name MC-Estrifan IH - Komponente B

(Contd. of page 2)

• Additional information For the wording of the listed hazard phrases refer to section 16.

## 4 First aid measures

· Description of first aid measures

• General information Instantly remove any clothing soiled by the product.

Take affected persons into the open air.

· After inhalation Supply fresh air.

After skin contact Instantly wash with water and soap and rinse thoroughly.
 After eye contact Rinse opened eye for several minutes under running water.

Seek medical treatment.

· After swallowing Drink copious amounts of water and provide fresh air. Instantly call

for doctor.

· Information for doctor

 Most important symptoms and effects, both acute and

delayed No further relevant information available.

Indication of any immediate medical attention and special

treatment needed No further relevant information available.

### 5 Firefighting measures

· Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· Special hazards arising from

the substance or mixture

No further relevant information available.

· Advice for firefighters

· Protective equipment: No special measures required.

#### 6 Accidental release measures

Personal precautions, protective equipment and

**Environmental precautions:** Wear protective equipment. Keep unprotected persons away. Prevent material from reaching sewage system, holes and cellars.

Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

- AE -



Page 4/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021 Version number 6 Revision: 17.10.2021

Trade name MC-Estrifan IH - Komponente B

(Contd. of page 3)

## 7 Handling and storage

· Handling

· Precautions for safe handling Store in cool, dry place in tightly closed containers.

Open and handle container with care.

· Information about protection

against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by

storerooms and containers: No special requirements.

· Information about storage in

one common storage facility: Not required.

· Further information about

**storage conditions:** Keep container tightly sealed.

· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· Additional information about

design of technical systems: No further data; see item 7.

· Control p	aramet	ders ders
· Compone	nts wit	th critical values that require monitoring at the workplace:
100-51-6	Benzyl	alcohol
WEEL (US	SA) Loi	ng-term value: 10 ppm
· DNELs		
15520-10-	2 2-me	thylpentane-1,5-diamine
Dermal	DNEL	1.5 mg/kg bw/day (ArL)
Inhalative	DNEL	0.25 mg/m³ (ArL)
		0.5 mg/m³ (Ark)
2855-13-2	3-amii	nomethyl-3,5,5-trimethylcyclohexylamine
Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
Inhalative	DNEL	20.1 mg/m³ (ArL)
100-51-6 I	Benzyl	alcohol
Oral	DNEL	4 mg/kg bw/Tag (ArL)
		20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL)
		40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m³ (ArL)
		110 mg/m³ (Ark)

(Contd. on page 5)





## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021 Version number 6 Revision: 17.10.2021

### Trade name MC-Estrifan IH - Komponente B

		(Contd. of p	
9046-1	0-0 Polyoxypropylenediamine		
Oral	DNEL 0.04 mg/kg bw/Tag (ArL)		
Derma	DNEL 2.5 mg/kg bw/day (ArL)		
	2 2,4,6-tris(dimethylaminomethyl)phen	ol	
Inhalat	ive DNEL 0.31 mg/m³ (ArL)		
<b>PNEC</b> :			
15520-	10-2 2-methylpentane-1,5-diamine		
PNEC	0.042 mg/l (Mew)		
	0.42 mg/l (Suw)		
2855-1	3-2 3-aminomethyl-3,5,5-trimethylcycl	ohexylamine	
PNEC	0.006 mg/l (Mew)		
	0.06 mg/l (Suw)		
PNEC	0.578 mg/kg dwt (Sediment)		
	5.784 mg/kg dwt (Fresh water sediment)		
	-6 Benzyl alcohol		
PNEC	0.527 mg/l (Marine water sediment)		
	0.1 mg/l (Mew)		
	1 mg/l (Fresh water sediment)		
PNEC	0.456 mg/kg dwt (Bod)		
	5.27 mg/kg dwt (Fresh water sediment)		
	0-0 Polyoxypropylenediamine		
PNEC	7.5 mg/l (Sewage Treatment Plant)		
	0.015 mg/l (Fresh water)		
	0.0176 mg/kg dwt (Bod)		
	0.125 mg/kg dwt (Sediment)		
	0.132 mg/kg dwt (Fresh water sediment)		
	2 2,4,6-tris(dimethylaminomethyl)phen	ol	
PNEC	0.2 mg/l (Sewage Treatment Plant)		
	0.0084 mg/l (Mew)		
	0.084 mg/l (Suw)		

- · Exposure controls
- · Personal protective equipment
- · General protective and

**hygienic measures** Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Protection of hands: Protective gloves.

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

(Contd. on page 6)

- AE



Page 6/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021 Version number 6 Revision: 17.10.2021

### Trade name MC-Estrifan IH - Komponente B

(Contd. of page 5)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove

material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses

Tightly sealed safety glasses.

· **Body protection:** Protective work clothing.

### 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Colour: Light yellow
Smell: Characteristic

· Change in condition

Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined

Flash point: 111 °CIgnition temperature: 380 °C

Self-inflammability: Product is not selfigniting.

• Explosive properties: Product is not explosive.

· Critical values for explosion:

 Lower:
 1.3 Vol %

 Upper:
 13.0 Vol %

 • Steam pressure at 20 °C:
 0.1 hPa

· Density at 20 °C 1.01 g/cm³

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix

· Other information No further relevant information available.

## 10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 7)



Page 7/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021 Version number 6 Revision: 17.10.2021

#### Trade name MC-Estrifan IH - Komponente B

(Contd. of page 6)

· Chemical stability

Thermal decomposition /

**conditions to be avoided:** No decomposition if used according to specifications.

· Possibility of hazardous

reactions No dangerous reactions known

• Conditions to avoid No further relevant information available. • Incompatible materials: No further relevant information available.

Hazardous decomposition

products: No dangerous decomposition products known

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

	values that are relevant	
15520-10-	2 2-methylpentane-1,5-	diamine
Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)
2855-13-2	3-aminomethyl-3,5,5-ti	rimethylcyclohexylamine
Oral	LD50	1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit)
		>2000 mg/kg (rat)
100-51-6	Benzyl alcohol	
Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)
9046-10-0	Polyoxypropylenediar	nine
Oral	LD50	2855 mg/kg (Rat)
Dermal	LD50	2980 mg/kg (Kan)
90-72-2 2,	4,6-tris(dimethylamino	methyl)phenol
Oral	LD50	2169 mg/kg (rat)
	NOAEL	15 mg/kg (rat)

Primary irritant effect:

· Skin corrosion/irritation Caustic effect on skin and mucous membranes.

· Serious eye damage/irritation Strong caustic effect.

Respiratory or skin

sensitisation Sensitization possible by skin contact.

(Contd. on page 8)



Page 8/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021 Version number 6 Revision: 17.10.2021

#### Trade name MC-Estrifan IH - Komponente B

· Additional toxicological

information:

(Contd. of page 7)

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for

Preparations as issued in the latest version:

Harmful Corrosive Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

## 12 Ecological information

· Toxicity

Aquatic to	xicity:
15520-10-2	2-methylpentane-1,5-diamine
EC50/72h	>100 mg/l (algae)
EC50	1825 mg/l (fish)
EC50/48h	19.8 mg/l (Daphnia magna)
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine
LC50/96h	110 mg/l (Leucidus idus)
EC50	1120 mg/l (Pseudomonas putida)
EC50/48h	23 mg/l (Daphnia magna)
NOEC	1.5 mg/l (Desmodesmus subspicatus)
	3 mg/l (Daphnia magna)
ErC50/72h	>50 mg/l (Desmodesmus subspicatus)
100-51-6 B	enzyl alcohol
IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)
	10 mg/l (Lepomis macrochirus)
90-72-2 2,4	,6-tris(dimethylaminomethyl)phenol
EC50/72h	84 mg/l (Desmodesmus subspicatus)
LC50/96h	175 mg/l (Cyp)
NOEC	2 mg/l (BEL)
	6.25 mg/l (Desmodesmus subspicatus)

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- Bioaccumulative potential
   Mobility in soil
   No further relevant information available.
   No further relevant information available.
- · Additional ecological information:
- General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

Results of PBT and vPvB assessment

· **PBT:** Not applicable.

(Contd. on page 9)



Page 9/11

(Contd. of page 8)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021 Version number 6 Revision: 17.10.2021

### Trade name MC-Estrifan IH - Komponente B

· **vPvB**: Not applicable.

Other adverse effects No further relevant information available.

## 13 Disposal considerations

· Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

UN-Number ADR, IMDG, IATA	UN2735
UN proper shipping name ADR, IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S. methylpentane-1,5-diamin ISOPHORONEDIAMINE)
Transport hazard class(es)	
ADR Class Label	8 (C7) Corrosive substances. 8
IMDG, IATA Class Label	8 Corrosive substances. 8
Packing group ADR, IMDG, IATA	II
Environmental hazards: Marine pollutant:	nein No
Special precautions for user Kemler Number: EMS Number:	Warning: Corrosive substances. 80 F-A,S-B
Segregation groups Stowage Category	Alkalis A
Segregation Code	SG35 Stow "separated from" SGG1-acids

(Contd. on page 10)



Page 10/11

## Safety data sheet according to 1907/2006/EC, Article 31

Revision: 17.10.2021 Printing date 23.10.2021 Version number 6

### Trade name MC-Estrifan IH - Komponente B

(Contd. of page 9)

· Transport/Additional information:

Limited quantities (LQ) 1L

· Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· Transport category · Tunnel restriction code

· Remarks: 1 kg Gebinde: Begrenzte Mengen

·IMDG

· Limited quantities (LQ)

Excepted quantities (EQ) Code: E2

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation": UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (2-

METHYLPENTANE-1.5-DIAMINE.

ISOPHORONEDIAMINE), 8, II

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous

substances - ANNEX I None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data

specification sheet: Environment protection department.

· Contact:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) (Contd. on page 11)



Page 11/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.10.2021 Version number 6 Revision: 17.10.2021

### Trade name MC-Estrifan IH - Komponente B

(Contd. of page 10)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 4: Flammable liquids – Category 4 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 5: Acute toxicity – Category 5

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 3

ΑE