

\*

Page 1/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2023

Version number 18

Revision: 08.07.2023

· Product identifier		
<ul> <li>Trade name</li> <li>Relevant identified uses of the substance or mixture and</li> </ul>	MC-Estrifan Color Protect Pro - Komponente B	
uses advised against · Application of the substance	No further relevant information available.	
/ the mixture	Coating compound/ Surface coating/ paint Hardening agent/ Curing agent	
• Details of the supplier of the s • Manufacturer/Supplier:	MC-Bauchemie Müller GmbH & Co. KG Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400	
	E-Mail: info@mc-bauchemie.de MC-Bauchemie AG	
	Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax : +44-7400533	
· Informing department:	msds@mc-bauchemie.de	
2 Hazards identification		
	ce or mixture	
· Classification of the substand		
	ustible liquid.	
Classification of the substandFlam. Liq. 4H227 CombuAcute Tox. 4H332 Harmfu	ustible liquid.	
Classification of the substandFlam. Liq. 4H227 CombuAcute Tox. 4H332 HarmfuSkin Irrit. 2H315 Cause	ustible liquid. ul if inhaled.	
Classification of the substand Flam. Liq. 4H227 Combu H332 Harmfu Skin Irrit. 2Skin Irrit. 2H315 Cause H317 May ca	ustible liquid. ul if inhaled. s skin irritation.	
Classification of the substand Flam. Liq. 4H227 Combu H332 Harmfu Skin Irrit. 2Skin Irrit. 2H335 Cause H317 May ca STOT SE 3	ustible liquid. ul if inhaled. s skin irritation. ause an allergic skin reaction.	
Classification of the substand Flam. Liq. 4H227 Combu H322 Harmfu Acute Tox. 4Acute Tox. 4H332 Harmfu Skin Irrit. 2Skin Irrit. 2H315 Cause H317 May ca STOT SE 3STOT SE 3H335 May ca H335 May ca Aquatic Chronic 3· Label elements· GHS label elements	ustible liquid. ul if inhaled. s skin irritation. ause an allergic skin reaction. ause respiratory irritation. ul to aquatic life with long lasting effects.	
Classification of the substand Flam. Liq. 4H227 Combu H332 Harmfu Acute Tox. 4Acute Tox. 4H332 Harmfu Skin Irrit. 2Skin Irrit. 2H315 Cause H317 May ca STOT SE 3STOT SE 3H335 May ca H335 May ca Aquatic Chronic 3H412 Harmfu· Label elements	ustible liquid. ul if inhaled. s skin irritation. ause an allergic skin reaction. ause respiratory irritation. ul to aquatic life with long lasting effects. The product is classified and labelled according to the Globali Harmonised System (GHS).	
<ul> <li>Classification of the substance Flam. Liq. 4 H227 Combu- Acute Tox. 4 H332 Harmfu Skin Irrit. 2 H315 Cause Skin Sens. 1 H317 May ca STOT SE 3 H335 May ca Aquatic Chronic 3 H412 Harmfu</li> <li>Label elements</li> <li>GHS label elements</li> <li>Hazard pictograms</li> </ul>	ustible liquid. ul if inhaled. s skin irritation. ause an allergic skin reaction. ause respiratory irritation. ul to aquatic life with long lasting effects. The product is classified and labelled according to the Global Harmonised System (GHS). GHS07	
<ul> <li>Classification of the substand Flam. Liq. 4 H227 Combu Acute Tox. 4 H332 Harmfu Skin Irrit. 2 H315 Cause Skin Sens. 1 H317 May ca STOT SE 3 H335 May ca Aquatic Chronic 3 H412 Harmfu</li> <li>Label elements</li> <li>GHS label elements</li> <li>Hazard pictograms</li> <li>Signal word</li> </ul>	ustible liquid. ul if inhaled. s skin irritation. ause an allergic skin reaction. ause respiratory irritation. ul to aquatic life with long lasting effects. The product is classified and labelled according to the Globall Harmonised System (GHS).	
<ul> <li>Classification of the substance Flam. Liq. 4 H227 Combu- Acute Tox. 4 H332 Harmfu Skin Irrit. 2 H315 Cause Skin Sens. 1 H317 May ca STOT SE 3 H335 May ca Aquatic Chronic 3 H412 Harmfu</li> <li>Label elements</li> <li>GHS label elements</li> <li>Hazard pictograms</li> </ul>	ustible liquid. ul if inhaled. s skin irritation. ause an allergic skin reaction. ause respiratory irritation. ul to aquatic life with long lasting effects. The product is classified and labelled according to the Globall Harmonised System (GHS). GHS07	



Page 2/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2023

Version number 18

Revision: 08.07.2023

#### Trade name MC-Estrifan Color Protect Pro - Komponente B

	(Contd. of page
	Harmful if inhaled.
	Causes skin irritation.
	May cause an allergic skin reaction.
	May cause respiratory irritation.
	Harmful to aquatic life with long lasting effects.
· Precautionary statements	Keep away from flames and hot surfaces. No smoking.
······	Avoid breathing dust/fume/gas/mist/vapours/spray.
	Wear protective gloves/protective clothing/eye protection/fac protection.
	IF INHALED: Remove person to fresh air and keep comfortable the breathing.
	Call a POISON CENTER/doctor if you feel unwell.
	Store in a well-ventilated place. Keep container tightly closed.
· Other hazards	,,
· Results of PBT and vPvB as	sessment

· PBT:

· vPvB:

- Not applicable. Not applicable.

### 3 Composition/information on ingredients

· Chemical characterisation: Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:			
160994-68-3	Hydrophiles, aliphatisches Polyisocyanat	80-100%	
	Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412		
3779-63-3	Hexamethylen-1,6-diisocyanat Homopolymer	≥1-<10%	
	Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335		
· Additional in	formation For the wording of the listed hazard phrases refer to sec	tion 16.	

#### 4 First aid measures

<ul> <li>Description of first aid measure</li> </ul>	ures
After inhalation	Supply fresh air.
<ul> <li>After skin contact</li> </ul>	Instantly wash with water and soap and rinse thoroughly.
· After eye contact	Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
· After swallowing	Rinse out mouth and then drink plenty of water. In case of persistent symptoms consult doctor.
<ul> <li>Information for doctor</li> <li>Most important symptoms and effects, both acute and</li> </ul>	
delayed	No further relevant information available.

(Contd. on page 3)

AE



Page 3/8

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2023

Version number 18

Revision: 08.07.2023

(Contd. of page 2)

#### Trade name MC-Estrifan Color Protect Pro - Komponente B

 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Firefighting measures

• Extinguishing media

- Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- Special hazards arising from the substance or mixture
   Advice for firefighters
- · Protective equipment:
- No special measures required.

No further relevant information available.

#### 6 Accidental release measures

<ul> <li>Personal precautions, protective equipment and</li> </ul>	
emergency procedures	Not required.
• Environmental precautions:	Inform respective authorities in case product reaches water or sewage system.
<ul> <li>Methods and material for</li> </ul>	
containment and cleaning up	: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
	Ensure adequate ventilation.
• Reference to other sections	See Section 7 for information on safe handling
	See Section 8 for information on personal protection equipment.
	See Section 13 for information on disposal.

#### 7 Handling and storage

· Handling

• **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by
- storerooms and containers: No special requirements.
- Information about storage in
- one common storage facility: Not required.
- Further information about storage conditions: None. Storage class 10

(Contd. on page 4)

<sup>-</sup> AE



Page 4/8

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2023

Version number 18

Revision: 08.07.2023

#### Trade name MC-Estrifan Color Protect Pro - Komponente B

Specific end use(s)

No further relevant information available.

(Contd. of page 3)

AF

8 Exposure controls/personal protection		
<ul> <li>Additional information about design of technical systems:</li> </ul>	No further data; see section 7.	
<ul> <li>Control parameters</li> <li>Components with critical values that require monitoring at the workplace:</li> <li>Additional information:</li> </ul>	The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace. The lists that were valid during the compilation were used as basis.	
<ul> <li>Exposure controls</li> <li>Personal protective equipmer</li> <li>General protective and</li> </ul>	nt	
hygienic measures	Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.	
· Breathing equipment:	Respiratory protection is required at inadequately ventilated workplaces and during spray processing. Fresh air masks or combination filters A2-P2 are recommended for short-term work.	
· Protection of hands:	Conditionally suitable materials for protective gloves; EN 374-3: Nitrile rubber - NBR: Thickness $\geq 0.35$ mm. Only suitable for splash protection. Only suitable for short-term exposure. In case of contamination, the protective gloves must be changed immediately.	
Material of gloves	Nitrile rubber, NBR	
Penetration time of glove     meterial	The exact break trough time has to be found out by the	
material	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.	
Eye protection:	Safety glasses	
· Body protection:	Protective work clothing.	

## 9 Physical and chemical properties

<ul> <li>Information on basic physical and</li> <li>General Information</li> </ul>	chemical properties	
· Appearance:		
Form:	Fluid	
Colour:	Colourless	
· Smell:	Characteristic	
· pH-value at 20 °C:	7	
Change in condition		
Melting point/freezing point: Initial boiling point and boiling ra	Not determined n <b>ge:</b> 175 °C	
		(Contd. on page



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2023

Version number 18

Revision: 08.07.2023

Page 5/8

#### Trade name MC-Estrifan Color Protect Pro - Komponente B

	(Contd. of page
70 °C	
Product is not selfigniting.	
Product is not explosive.	
Not determined.	
1.15 g/cm³	
Not miscible or difficult to mix	
2000 mPas Not determined.	
	Product is not selfigniting.Product is not explosive.Not determined.1.15 g/cm³Not miscible or difficult to mix2000 mPas

0 Stability and reactivity	
Reactivity Chemical stability	No further relevant information available.
<ul> <li>Thermal decomposition / conditions to be avoided:</li> <li>Possibility of hazardous</li> </ul>	No decomposition if used according to specifications.
reactions	Reacts with amines
· Conditions to avoid	No further relevant information available.
<ul> <li>Incompatible materials:</li> <li>Hazardous decomposition</li> </ul>	No further relevant information available.
products:	No dangerous decomposition products known

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

	-	
<ul> <li>LD/LC50 values that are relevant for classification:</li> </ul>		
160994-68-3 Hydrophiles, aliphatisches Polyisocyanat		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	0.39 mg/l (rat)
	<b>160994-68</b> Oral Dermal	<b>160994-68-3 Hydrop</b> Oral LD50

Primary irritant effect:

· Serious eye damage/irritation No irritant effect.

· Respiratory or skin sensitisation

No sensitizing effect known.

(Contd. on page 6)

AE



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2023

Version number 18

Revision: 08.07.2023

(Contd. of page 5)

Page 6/8

#### Trade name MC-Estrifan Color Protect Pro - Komponente B

 Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version: *Irritant* 

· Toxicity		
· Aquatic tox	icity:	
160994-68-3	3 Hydrophiles, al	liphatisches Polyisocyanat
LC50/96h	28.3 mg/l (Danio I	rerio)
EC50	>10000 mg/l (BEL	_)
EC50/48h	>100 mg/l (Daphr	nia magna)
ErC50/72h	>100 mg/l (Scene	edesmus subspicatus)
· Bioaccumu · Mobility in : · Ecotoxical	soil	No further relevant information available. No further relevant information available.
<ul> <li>Remark:</li> <li>Additional ecological information</li> </ul>		Harmful to fish
· General not		Harmful to aquatic organisms Do not allow undiluted product or large quantities of it to reac ground water, water bodies or sewage system.
· Results of I	PBT and vPvB as	
· PBT:		Not applicable.
· vPvB:		Not applicable.

#### 13 Disposal considerations

· Waste treatment methods	
· Recommendation	Must not be disposed of together with household garbage. Do not
· Waste disposal key number:	allow product to reach sewage system. 08 01 11 * Farb- und Lackabfälle, die organische Lösemittel oder andere gefährliche Stoffe enthalten.
· Uncleaned packagings:	
· Recommendation:	Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.
	Produktreste mit Wasser mischen, aushärten lassen und als
	Bauschutt entsorgen.
	(Contd. on page 7)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2023

Version number 18

Solvent naphtha

Revision: 08.07.2023

(Contd. of page 6)

Page 7/8

Trade name MC-Estrifan Color Protect Pro - Komponente B

 Recommended cleaning agent:

14 Transport information · UN-Number · ADR, ADN, IMDG, IATA Void · UN proper shipping name ADR, ADN, IMDG, IATA Void · Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class Void · Packing group ADR, IMDG, IATA Void · Environmental hazards: · Marine pollutant: No Special precautions for user Not applicable. · Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · UN "Model Regulation": Void

#### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- Named dangerous
- substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing data
- specification sheet: Environment protection department.
- · Contact:
- Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 8)

AE



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.07.2023

Version number 18

Revision: 08.07.2023

Page 8/8

## Trade name MC-Estrifan Color Protect Pro - Komponente B

	(Contd. of page
	ICAO: International Civil Aviation Organisation
	ADR: Accord relatif au transport international des marchandises dangereuses p
	route (European Agreement Concerning the International Carriage of Dangerou Goods by Road)
	IMDG: International Maritime Code for Dangerous Goods
	IATA: International Air Transport Association
	EINECS: European Inventory of Existing Commercial Chemical Substances
	ELINCS: European List of Notified Chemical Substances
	CAS: Chemical Abstracts Service (division of the American Chemical Society)
	LC50: Lethal concentration, 50 percent
	LD50: Lethal dose, 50 percent
	PBT: Persistent, Bioaccumulative and Toxic
	vPvB: very Persistent and very Bioaccumulative
	Flam. Lig. 4: Flammable liquids – Category 4
	Acute Tox. 4: Acute toxicity – Category 4
	Skin Irrit. 2: Skin corrosion/irritation – Category 2
	Skin Sens. 1: Skin sensitisation – Category 1
	STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
	Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquat
	hazard – Category 3
• * Data compared to the	
previous version altered.	