

Page 1/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 23.03.2024 Printing date 23.03.2024 Version number 24

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name MC-Fastpack 1264 compact - Komponente A

· Relevant identified uses of the substance or mixture and

uses advised against

No further relevant information available.

Application of the substance

/ the mixture Epoxy resin Injektion

· Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

> Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department: msds@mc-bauchemie.de

2 Hazards identification

· Classification of the substance or mixture

H315 Causes skin irritation. Skin Irrit. 2

Serious eye damage/irritation - Category 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· Label elements

· GHS label elements The product is classified and labelled according to the Globally

Harmonised System (GHS).

· Hazard pictograms



GHS09 GHS07

· Signal word Warning

· Hazard-determining

components of labelling: epoxide derivates

Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]

dioxirane

(Contd. on page 2)



Page 2/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024 Version number 24 Revision: 23.03.2024

Trade name MC-Fastpack 1264 compact - Komponente A

(Contd. of page 1)

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane

(1:2)

· Hazard statements Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

• Precautionary statements Avoid breathing dust/fume/gas/mist/vapours/spray.

Avoid release to the environment.

Wear protective gloves / eye protection / face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

· Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterisation: Mixtures

• **Description:** Resin mixture with colouring agents.

Mixture consisting of the following components.

· Dangerous compo	onents:	
CAS: 1675-54-3	epoxide derivates Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	60-80%
CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	10-30%
CAS: 68609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives Skin Irrit. 2, H315; Skin Sens. 1, H317	10-30%
CAS: 9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317; Acute Tox. 5, H303; Acute Tox. 5, H313	≥2.5-<10%
CAS: 933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<2.5%

• Additional information For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)



Page 3/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024 Version number 24 Revision: 23.03.2024

Trade name MC-Fastpack 1264 compact - Komponente A

(Contd. of page 2)

4 First aid measures

· Description of first aid measures

• General information Remove contaminated clothing immediately. Consult a doctor if

symptoms occur. Move affected person to fresh air.

· After inhalation Supply fresh air; seek medical advice if symptoms occur.

If unconscious, place in recovery position and seek medical advice.

• After skin contact In case of contact with skin, wash carefully with plenty of soap and

water. Consult a doctor in case of skin reactions.

• After eye contact Rinse opened eye for several minutes under running water.

Call a doctor immediately

· After swallowing Rinse mouth with water. Never give anything by mouth to an

unconscious person. DO NOT induce vomiting. If symptoms

persist, consult a doctor.

· Information for doctor

· Most important symptoms and effects, both acute and

delayed Advice for the doctor: Elementary aid, decontamination,

symptomatic treatment.

5 Firefighting measures

· Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

· Special hazards arising from

the substance or mixture No further relevant information available.

· Advice for firefighters

· **Protective equipment:** No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and

emergency procedures Not required.

• Environmental precautions: Prevent material from reaching sewage system, holes and cellars.

· Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

• Reference to other sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

7 Handling and storage

· Handling

· Precautions for safe handling Open and handle containers with care.

Only use in well-ventilated areas (e.g. open construction, outdoor

(Contd. on page 4)



Page 4/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024 Version number 24 Revision: 23.03.2024

Trade name MC-Fastpack 1264 compact - Komponente A

(Contd. of page 3)

areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required.

are required.

Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins. Open and handle containers with care.

· Information about protection

against explosions and fires: Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic

discharges.

· Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Further information about

storage conditions: None.
Storage class 10

8 Exposure controls/personal protection

· Additional information about

design of technical systems: No further data; see section 7.

· Control parameters

Components with critical values that require monitoring at the workplace:
· · · · · · · · · · · · · · · · · · ·
CAS: 100-51-6 Benzyl alcohol
WEEL (USA) Long-term value: 10 ppm

· DNELs

CAS: 100-51-6 Benzyl alcohol

Orai	DNEL	4 mg/kg bw/ rag (ArL)
		4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL)
		8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m³ (ArL)
		110 mg/m³ (Ark)

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives

Oral	DNEL	1 mg/kg bw/Tag (ArL)
Dermal	DNEL	1 mg/kg bw/Tag (ArL) 1.7 mg/kg bw/day (ArL)
Inhalative	DNEL	0.98 mg/m³ (ArL)

(Contd. on page 5)



Page 5/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024 Version number 24 Revision: 23.03.2024

Trade name MC-Fastpack 1264 compact - Komponente A

(Contd. of page 4)

· PNECs

CAS: 100-51-6 Benzyl alcohol

PNEC | 0.527 mg/l (Marine water sediment)

0.1 mg/l (Mew)

1 mg/l (Fresh water sediment)

PNEC 0.456 mg/kg dwt (Bod)

5.27 mg/kg dwt (Fresh water sediment)

CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives

PNEC | 0.00072 mg/l (Mew)

0.0072 mg/l (Freshwater)

PNEC 80.12 mg/kg dwt (Bod)

6.677 mg/kg dwt (Sediment)

66.77 mg/kg dwt (Fresh water sediment)

Additional information:

The lists that were valid during the compilation were used as basis.

· Exposure controls

· Personal protective equipment

· General protective and

hygienic measures Keep away from food, drink and animal feed.

Remove soiled, soaked clothing immediately.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

Breathing equipment: If workplace limit values cannot be complied with by ventilation

measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction

with BGR 190.

• Protection of hands: Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

· Material of gloves You can find help with choosing gloves on the website https://

www.bgbau.de/fileadmin/Gisbau/Projekte.pdf

For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to

manufacturer. As the product

is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be

checked before use.

Nitrile rubber

Recommended material thickness:≥ 0.4 mm

Penetration time of glove

material

The breakthrough times of the Sol-vex 37-900 protective gloves

are around 8 hours.

(Contd. on page 6)



Page 6/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024 Version number 24 Revision: 23.03.2024

Trade name MC-Fastpack 1264 compact - Komponente A

(Contd. of page 5)

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective

glove manufacturer and adhered to.

Nitrile rubber

Material thickness: ≥ 0.40 mm Penetration time: ≥ 480 min

Butyl rubber:

Material thickness: ≥ 0.5 mm Penetration time: ≥ 480 min Tight-fitting safety goggles.

Safety goggles.

Body protection: Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the

lower leg area should be protected by protective trousers.

9 Physical and chemical properties

· General Information

· Appearance:

· Eye protection:

Form: Fluid
Colour: Transparent
Smell: Characteristic

pH-value: Not determined.

· Change in condition

Melting point/freezing point: Not determined

Initial boiling point and boiling range: >200 °C

· Flash point: 101 °C

· Auto-ignition temperature: 184 °C

· Self-inflammability: Product is not selfigniting.

• Explosive properties: Product is not explosive.

· Critical values for explosion:

 Lower:
 1.3 Vol %

 Upper:
 13 Vol %

• Steam pressure at 20 °C: 0.1 hPa • Vapour pressure at 50 °C: 0.7 hPa

Density at 20 °C 1.12 g/cm³

(Contd. on page 7)



Page 7/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 23.03.2024 Printing date 23.03.2024 Version number 24

Trade name MC-Fastpack 1264 compact - Komponente A

(Contd. of page 6)

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix

· Viscosity:

dynamic: Not determined. kinematic at 20 °C: 138 s (DIN 53211/4)

· Other information

No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

· Chemical stability

Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous

reactions

No dangerous reactions known

· Conditions to avoid · Incompatible materials: No further relevant information available. No further relevant information available.

· Hazardous decomposition

products: No dangerous decomposition products known

11 Toxicological information

Information on toxicological effects

· Acute tox	icity	
· LD/LC50	values that are relevant	t for classification:
CAS: 167	5-54-3 epoxide derivate	es
Dermal	LD50	23000 mg/kg (rabbit)
CAS: 100-	-51-6 Benzyl alcohol	
Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)
CAS: 68609-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives		[(C12-14-alkyloxy)methyl] derivatives
Oral	LD50	17100 mg/kg (rat)

(Contd. on page 8)



Page 8/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024 Version number 24 Revision: 23.03.2024

Trade name MC-Fastpack 1264 compact - Komponente A

(Contd. of page 7)

CAS: 9003-36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'[methylenebis(2,1-phenyleneoxymethylene)]dioxirane

 Oral
 LD50
 >2000 mg/kg (rat)

 Dermal
 LD50
 >2000 mg/kg (rabbit)

· Primary irritant effect:

• **Skin corrosion/irritation** Irritant for skin and mucous membranes.

· Serious eye damage/irritation No irritant effect.

· Respiratory or skin

sensitisation Sensitization possible by skin contact.

· Additional toxicological

information: The product shows the following dangers according to the

calculation method of the General EC Classification Guidelines for

Preparations as issued in the latest version:

Irritant

12 Ecological information

·Toxicity

· I oxicity	
· Aquatic to	kicity:
CAS: 1675-	54-3 epoxide derivates
IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)
CAS: 100-5	1-6 Benzyl alcohol
IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)
	10 mg/l (Lepomis macrochirus)
CAS: 68609	9-97-2 Oxirane, mono[(C12-14-alkyloxy)methyl] derivatives
EbC50/72h	843 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>5000 mg/l (Oncorhynchus mykiss)
	1800 mg/l (Lepomis macrochirus)
EC50	>100 mg/l (BEL)
NOEC	500 mg/l (Pseudokirchneriella subcapitata)
CAS: 9003-	36-5 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane
LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)

- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.

(Contd. on page 9)



Page 9/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024 Version number 24 Revision: 23.03.2024

Trade name MC-Fastpack 1264 compact - Komponente A

(Contd. of page 8)

· **Mobility in soil** No further relevant information available.

· Additional ecological information:

• General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

UN-Number ADR, IMDG, IATA	UN3082
UN proper shipping name ADR, IATA IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (epoxide derivates, Oxiran mono[(C12-14-alkyloxy)methyl] derivatives) ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (epoxide derivates, Oxiran mono[(C12-14-alkyloxy)methyl] derivatives), MARII
Transport horough along (as)	POLLUTANT
Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous dangerous substances a articles.
Label	9
IMDG, IATA	
Class	9 Miscellaneous dangerous substances and articles
Label	9
Packing group	
ADR, IMDG, IATA	III



Page 10/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024 Version number 24 Revision: 23.03.2024

Trade name MC-Fastpack 1264 compact - Komponente A

(Contd. of page 9)

· Environmental hazards: · Marine pollutant:

· Marine pollutant: Yes

Symbol (fish and tree)
Special marking (ADR):
Special marking (IATA):
Symbol (fish and tree)
Symbol (fish and tree)

· Special precautions for user Warning: Miscellaneous dangerous substances and

articles.

Kemler Number:
 EMS Number:
 Stowage Category

· Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category 3 · Tunnel restriction code (-)

Remarks: 1 kg Gebinde:Begrenzte Mengen

· IMDG

· Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 3082 ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES, OXIRANE, MONO[(C12-14-

ALKYLOXY)METHYL] DERIVATIVES), 9, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous

substances - ANNEX I None of the ingredients is listed.

• Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

(Contd. on page 11)



Page 11/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024 Version number 24 Revision: 23.03.2024

Trade name MC-Fastpack 1264 compact - Komponente A

(Contd. of page 10)

Qualifying quantity (tonnes) for the application of upper-

tier requirements 500 t

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data

specification sheet: Environment protection department.

· Contact:

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 5: Acute toxicity – Category 5

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Serious eye damage/irritation - Category 2A: Serious eye damage/eye irritation -

Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 3

* Data compared to the previous version altered.

ΑE