



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2021

Version number 12



Revision: 25.10.2021

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name** **MC-Floor Connect Adhesive - Komponente A**
- **Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- **Application of the substance / the mixture** Epoxy coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de
- **Informing department:** MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533
- **Emergency telephone number:** msds@mc-bauchemie.de
Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

2 Hazards identification

- **Classification of the substance or mixture**
 - Skin Irrit. 2 H315 Causes skin irritation.
 - Eye Irrit. 2A H319 Causes serious eye irritation.
 - Skin Sens. 1 H317 May cause an allergic skin reaction.
 - Aquatic Acute 3 H402 Harmful to aquatic life.
 - Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**

GHS07 GHS09
- **Signal word** Warning
- **Hazard-determining components of labelling:** Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues
molecular weight < 700

(Contd. on page 2)

AE

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2021

Version number 12

Revision: 25.10.2021

Trade name MC-Floor Connect Adhesive - Komponente A

	(Contd. of page 1)
	2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700
	1,6-hexene-diglycidylether
· Hazard statements	Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Harmful to aquatic life.
· Precautionary statements	Toxic to aquatic life with long lasting effects. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid release to the environment. Wear protective gloves / eye protection / face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.
· Other hazards	
· Results of PBT and vPvB assessment	
· PBT:	Not applicable.
· vPvB:	Not applicable.

3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥5-<25%
9003-36-5	2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; Acute Tox. 5, H303; Acute Tox. 5, H313; Aquatic Acute 2, H401	≥2.5-<10%
7631-86-9	silicon dioxide, chemically prepared Acute Tox. 5, H313	<5%
16096-31-4	1,6-hexene-diglycidylether Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; Acute Tox. 5, H313; Aquatic Acute 3, H402; Aquatic Chronic 3, H412	≥2.5-<5%
	Hydrophobes Siliziumdioxid, synthetisch, amorph Acute Tox. 5, H313	<2.5%
100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332	<2.5%
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318; Acute Tox. 5, H313	≥1-<1.5%

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2021

Version number 12

Revision: 25.10.2021

Trade name MC-Floor Connect Adhesive - Komponente A

		(Contd. of page 2)
13463-67-7	titanium dioxide Carc. 2, H351; Acute Tox. 5, H333	≥0.1-<1%
123-26-2	N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<0.5%
222417-26-7	Polyacrylate Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	≥0.025-<0.25%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· **Description of first aid measures**

· **After inhalation**

Supply fresh air and call for doctor for safety reasons.
In case of unconsciousness bring patient into stable side position for transport.

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.
Instantly rinse with water.

· **After eye contact**

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

· **After swallowing**

In case of persistent symptoms consult doctor.

· **Information for doctor**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Firefighting measures

· **Extinguishing media**

· **Suitable extinguishing agents** Use fire fighting measures that suit the environment.

· **Special hazards arising from the substance or mixture**

No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:**

No special measures required.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Not required.

· **Environmental precautions:**

Inform respective authorities in case product reaches water or sewage system.

(Contd. on page 4)

AE

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2021

Version number 12

Revision: 25.10.2021

Trade name MC-Floor Connect Adhesive - Komponente A

(Contd. of page 3)

- **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

7 Handling and storage

- **Handling**
- **Precautions for safe handling** Store in cool, dry place in tightly closed containers.
Open and handle container with care.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Do not store together with acids.
- **Further information about storage conditions:** Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

100-51-6 Benzyl alcohol

WEEL (USA) Long-term value: 10 ppm

· **DNELs**

7631-86-9 silicon dioxide, chemically prepared

Inhalative DNEL 4 mg/m³ (ArL)

16096-31-4 1,6-hexene-diglycidylether

Dermal DNEL 2.8 mg/kg bw/day (ArL)

Inhalative DNEL 4.9 mg/m³ (ArL)

100-51-6 Benzyl alcohol

Oral DNEL 4 mg/kg bw/Tag (ArL)

20 mg/kg bw/Tag (Ark)

(Contd. on page 5)



BE SURE. BUILD SURE.

Page 5/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2021

Version number 12

Revision: 25.10.2021

Trade name MC-Floor Connect Adhesive - Komponente A

(Contd. of page 4)

Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL) 110 mg/m ³ (Ark)

· PNECs

16096-31-4 1,6-hexene-diglycidylether

PNEC	0.0115 mg/l (Fresh water) 0.00115 mg/l (Mew)
PNEC	0.223 mg/kg dwt (Bod) 0.0283 mg/kg dwt (Sediment) 0.283 mg/kg dwt (Fresh water sediment)

100-51-6 Benzyl alcohol

PNEC	0.527 mg/l (Marine water sediment) 0.1 mg/l (Mew) 1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod) 5.27 mg/kg dwt (Fresh water sediment)

· Additional information: The lists that were valid during the compilation were used as basis.

· Exposure controls

· Personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.
Wash hands during breaks and at the end of the work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Protection of hands:

Protective gloves.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses
Tightly sealed safety glasses.

(Contd. on page 6)

— AE —



BE SURE. BUILD SURE.

Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2021

Version number 12

Revision: 25.10.2021

Trade name MC-Floor Connect Adhesive - Komponente A

· **Body protection:** Protective work clothing.

(Contd. of page 5)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	Whitish
Smell:	Characteristic

· **pH-value:** Not applicable.

· **Change in condition**

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	>200 °C

· **Flash point:** 151 °C

· **Self-inflammability:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive.

· **Steam pressure at 20 °C:** 0.1 hPa

· **Density at 20 °C** 1.8 g/cm³

· **Solubility in / Miscibility with**

Water:	Not miscible or difficult to mix
--------	----------------------------------

· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **Possibility of hazardous reactions**

No dangerous reactions known

· **Conditions to avoid**

No further relevant information available.

· **Incompatible materials:**

No further relevant information available.

· **Hazardous decomposition products:**

No dangerous decomposition products known

— AE —

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2021

Version number 12

Revision: 25.10.2021

Trade name MC-Floor Connect Adhesive - Komponente A

(Contd. of page 6)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity

· LD/LC50 values that are relevant for classification:

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Dermal	LD50	23000 mg/kg (rabbit)
--------	------	----------------------

9003-36-5 2,2'-[methylenebis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

7631-86-9 silicon dioxide, chemically prepared

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

16096-31-4 1,6-hexene-diglycidylether

Oral	LD50	>8500 mg/kg (rat)
Dermal	LD50	>4900 mg/kg (rat)

Hydrophobes Siliziumdioxid, synthetisch, amorph

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Oral	LD50	8030 mg/kg (rat)
Dermal	LD50	4248 mg/kg (rabbit)

13463-67-7 titanium dioxide

Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Irritant for skin and mucous membranes.
- Serious eye damage/irritation Irritant effect.
- Respiratory or skin sensitisation Sensitization possible by skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

(Contd. on page 8)



BE SURE. BUILD SURE.

Page 8/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2021

Version number 12

Revision: 25.10.2021

Trade name MC-Floor Connect Adhesive - Komponente A

Irritant

(Contd. of page 7)

12 Ecological information

· Toxicity

· Aquatic toxicity:

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Senastrum capricornutum)

9003-36-5 2,2'-[methylenbis(p-phenyleneoxymethylene)]bisoxirane polymers and homologues, molecular weight < 700

LC50/96h	>100 mg/l (Daphnia magna)
EC50/96h	>100 mg/l (Leucidus idus)

7631-86-9 silicon dioxide, chemically prepared

IC50/72h	440 mg/l (Senastrum capricornutum)
EC50/24h	>10000 mg/l (Daphnia magna)
LC50/96h	>5000 mg/l (Danio rerio)
	5000 mg/l (Brachydanio rerio)
EC50/48h	7600 mg/l (Ceriodaphnia dubia)
	120 mg/l (Senastrum capricornutum)
NOEC	60 mg/l (Senastrum capricornutum)

16096-31-4 1,6-hexene-diglycidylether

LC50/96h	30 mg/l (Leucidus idus)
EC50/48h	47 mg/l (Daphnia magna)

Hydrophobes Siliziumdioxid, synthetisch, amorph

Sensitisation	EL50	10000 mg/l (Daphnien)
	LC50/96h	>10000 mg/l (Brachydanio rerio)

100-51-6 Benzyl alcohol

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas)
	10 mg/l (Lepomis macrochirus)

2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

LC50/96h	55 mg/l (Cyp)
EC50/48h	473 mg/l (Daphnia magna)
ErC50/72h	255 mg/l (Scenedesmus subspicatus)

· **Persistence and degradability** No further relevant information available.

· **Behaviour in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

(Contd. on page 9)

AE

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2021

Version number 12

Revision: 25.10.2021

Trade name MC-Floor Connect Adhesive - Komponente A

(Contd. of page 8)

- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
Do not allow product to reach ground water, water bodies or
sewage system.
Danger to drinking water if even small quantities leak into soil.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not
allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · UN-Number · ADR, IMDG, IATA | <p>UN3082</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · ADR, IATA · IMDG | <p>ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (epoxide derivatives)
ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (epoxide derivatives), MARINE
POLLUTANT</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · ADR · Class · Label | <p>9 (M6) Miscellaneous dangerous substances and
articles.
9</p> |
| <ul style="list-style-type: none"> · IMDG, IATA · Class · Label | <p>9 Miscellaneous dangerous substances and articles.
9</p> |
| <ul style="list-style-type: none"> · Packing group · ADR, IMDG, IATA | <p>III</p> |

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2021

Version number 12

Revision: 25.10.2021

Trade name MC-Floor Connect Adhesive - Komponente A

(Contd. of page 9)

· Environmental hazards:	
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
· Kemler Number:	90
· EMS Number:	F-A, S-F
· Stowage Category	A
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE DERIVATES), 9, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture	
· Directive 2012/18/EU	
· Named dangerous substances - ANNEX I	None of the ingredients is listed.
· Seveso category	E2 Hazardous to the Aquatic Environment
· Qualifying quantity (tonnes) for the application of lower-tier requirements	200 t
· Qualifying quantity (tonnes) for the application of upper-tier requirements	500 t

(Contd. on page 11)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.11.2021

Version number 12

Revision: 25.10.2021

Trade name MC-Floor Connect Adhesive - Komponente A

(Contd. of page 10)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing data**

specification sheet:

Environment protection department.

· **Contact:**

· **Abbreviations and acronyms:** RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 5: Acute toxicity – Category 5
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

— AE