

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name** **MC-Floor Connect Adhesive - Komponente B**
- **Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- **Application of the substance / the mixture** Epoxy coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533
- **Informing department:** msds@mc-bauchemie.de

2 Hazards identification

- **Classification of the substance or mixture**
- Flam. Liq. 4 H227 Combustible liquid.
- Acute Tox. 4 H302 Harmful if swallowed.
- Acute Tox. 4 H312 Harmful in contact with skin.
- Acute Tox. 5 H333 May be harmful if inhaled.
- Skin Corr. 1A H314 Causes severe skin burns and eye damage.
- Eye Dam. 1 H318 Causes serious eye damage.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Repr. 2 H361 Suspected of damaging fertility or the unborn child.
- STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
- Aquatic Acute 3 H402 Harmful to aquatic life.
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS05 GHS07 GHS08

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labelling:**
 - polymer amine terminated
 - Isophorone diamine
 - Benzyl alcohol
 - 2-piperazin-1-ylethylamine
 - 2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid
- **Hazard statements**
 - Combustible liquid.
 - Harmful if swallowed.
 - Harmful in contact with skin.
 - May be harmful if inhaled.
 - Causes severe skin burns and eye damage.
 - May cause an allergic skin reaction.
 - Suspected of damaging fertility or the unborn child.
 - May cause damage to organs through prolonged or repeated exposure.
 - Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
 - Do not breathe dusts or mists.
 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - Immediately call a POISON CENTER/doctor.
 - Specific treatment (see on this label).
 - Take off contaminated clothing and wash it before reuse.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

	polymer amine terminated Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317	10-30%
CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	10-30%
CAS: 61788-44-1	2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Acute 2, H401	≥10-<25%
CAS: 2855-13-2	Isophorone diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥10-<25%

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 2)		
CAS: 15520-10-2	2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335; Flam. Liq. 4, H227	≥10-<20%
CAS: 140-31-8	2-piperazin-1-ylethylamine Acute Tox. 3, H311; Repr. 2, H361; STOT RE 1, H372; Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥5-<10%
CAS: 9046-10-0	Polyoxypropylenediamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 5, H303; Acute Tox. 5, H313; Aquatic Chronic 3, H412	≥3-<5%
CAS: 8028-48-6	Orange juice oil Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Acute 2, H401	≥0.25-<1%
CAS: 140-31-8	Aminoethylpiperazine Acute Tox. 3, H311; Repr. 2, H361; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317; Flam. Liq. 4, H227; Aquatic Chronic 3, H412	≥0.1-<1%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· **Description of first aid measures**

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur.
If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water.
Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· **Information for doctor**

· **Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
- **Environmental precautions:** Wear protective equipment. Keep unprotected persons away. Inform respective authorities in case product reaches water or sewage system.
- **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

7 Handling and storage

- **Handling**
- **Precautions for safe handling** Open and handle containers with care. Only use in well-ventilated areas (e.g. open construction, outdoor areas), in rooms without air exchange (e.g. closed rooms, underground car parks) ventilation measures are required. Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins. Open and handle containers with care.
- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Further information about storage conditions:** Keep container tightly closed in a well-ventilated place.

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

· **Storage class**

8A

(Contd. of page 4)

8 Exposure controls/personal protection

· **Additional information about**

design of technical systems: No further data; see section 7.

· **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

CAS: 100-51-6 Benzyl alcohol

WEEL (USA) Long-term value: 10 ppm

· **DNELs**

CAS: 100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
------	------	---

Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
--------	------	---

Inhalative	DNEL	22 mg/m ³ (ArL) 110 mg/m ³ (Ark)
------------	------	---

CAS: 2855-13-2 Isophorone diamine

Oral	DNEL	0.526 mg/kg bw/Tag (ArL)
------	------	--------------------------

Inhalative	DNEL	20.1 mg/m ³ (ArL)
------------	------	------------------------------

CAS: 15520-10-2 2-methylpentane-1,5-diamine

Dermal	DNEL	1.5 mg/kg bw/day (ArL)
--------	------	------------------------

Inhalative	DNEL	0.25 mg/m ³ (ArL) 0.5 mg/m ³ (Ark)
------------	------	---

CAS: 140-31-8 2-piperazin-1-ylethylamine

Dermal	DNEL	3.33 mg/kg bw/day (ArL)
--------	------	-------------------------

Inhalative	DNEL	10.6 mg/m ³ (ArL)
------------	------	------------------------------

CAS: 9046-10-0 Polyoxypropylenediamine

Oral	DNEL	0.04 mg/kg bw/Tag (ArL)
------	------	-------------------------

Dermal	DNEL	2.5 mg/kg bw/day (ArL)
--------	------	------------------------

CAS: 8028-48-6 Orange juice oil

Oral	DNEL	4.44 mg/kg bw/Tag (ArL)
------	------	-------------------------

Dermal	DNEL	8.89 mg/kg bw/day (ArL)
--------	------	-------------------------

Inhalative	DNEL	31.1 mg/m ³ (ArL)
------------	------	------------------------------

CAS: 140-31-8 Aminoethylpiperazine

Dermal	DNEL	3.33 mg/kg bw/day (ArL)
--------	------	-------------------------

Inhalative	DNEL	10.6 mg/m ³ (ArL)
------------	------	------------------------------

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 5)

· PNECs

CAS: 100-51-6 Benzyl alcohol

PNEC	0.527 mg/l (Marine water sediment)
	0.1 mg/l (Mew)
	1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod)
	5.27 mg/kg dwt (Fresh water sediment)

CAS: 2855-13-2 Isophorone diamine

PNEC	0.006 mg/l (Mew)
	0.06 mg/l (Freshwater)
PNEC	0.578 mg/kg dwt (Sediment)
	5.784 mg/kg dwt (Fresh water sediment)

CAS: 15520-10-2 2-methylpentane-1,5-diamine

PNEC	0.042 mg/l (Mew)
	0.42 mg/l (Freshwater)

CAS: 140-31-8 2-piperazin-1-ylethylamine

PNEC	250 mg/l (Kla)
	0.0058 mg/l (Mew)
	0.058 mg/l (Freshwater)
PNEC	1 mg/kg dwt (Bod)
	21.5 mg/kg dwt (Sediment)
	215 mg/kg dwt (Fresh water sediment)

CAS: 9046-10-0 Polyoxypropylenediamine

PNEC	7.5 mg/l (Sewage Treatment Plant)
	0.015 mg/l (Fresh water)
PNEC	0.0176 mg/kg dwt (Bod)
	0.125 mg/kg dwt (Sediment)
	0.132 mg/kg dwt (Fresh water sediment)

CAS: 140-31-8 Aminoethylpiperazine

PNEC	250 mg/l (Kla)
	0.0058 mg/l (Mew)
	0.058 mg/l (Freshwater)
PNEC	1 mg/kg dwt (Bod)
	21.5 mg/kg dwt (Sediment)
	215 mg/kg dwt (Fresh water sediment)

· Additional information: The lists that were valid during the compilation were used as basis.

· Exposure controls

· Personal protective equipment

· General protective and hygienic measures

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 6)

- Breathing equipment:** Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.
If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.
- Protection of hands:** Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves** You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.
Nitrile rubber
Recommended material thickness: ≥ 0.4 mm
- Penetration time of glove material** The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.
The following applies to all other gloves:
The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.
Nitrile rubber
Material thickness: ≥ 0.40 mm
Penetration time: ≥ 480 min
Butyl rubber:
Material thickness: ≥ 0.5 mm
Penetration time: ≥ 480 min
- Eye protection:** Tight-fitting safety goggles.
Safety goggles.
- Body protection:** Protective clothing
Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

AE

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 7)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	Whitish
Smell:	Characteristic

· **pH-value at 20 °C:** 12.5

· **Change in condition**

Melting point/freezing point: Not determined
Initial boiling point and boiling range: 193 °C

· **Flash point:** 83 °C

· **Self-inflammability:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive.

· **Critical values for explosion:**

Lower: 1.3 Vol %
Upper: 13 Vol %

· **Steam pressure at 20 °C:** 0.1 hPa

· **Vapour pressure at 50 °C:** 0.7 hPa

· **Density at 20 °C** 1.02 g/cm³

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix

· **Viscosity:**

dynamic at 20 °C: 100 mPas
kinematic: Not determined.

· **Other information**

No further relevant information available.

10 Stability and reactivity

· **Reactivity**

No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **Possibility of hazardous reactions**

No dangerous reactions known

· **Conditions to avoid**

No further relevant information available.

· **Incompatible materials:**

No further relevant information available.

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 8)

· **Hazardous decomposition products:**

No dangerous decomposition products known

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity**

· **LD/LC50 values that are relevant for classification:**

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse) 200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

CAS: 2855-13-2 Isophorone diamine

Oral	LD50	1030 mg/kg (ATE) 1030 mg/kg (rat)
	NOAEL	250 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit) >2000 mg/kg (rat)

CAS: 15520-10-2 2-methylpentane-1,5-diamine

Oral	LD50	1170 mg/kg (rat)
Dermal	LD50	1870 mg/kg (rabbit)
Inhalative	LC50/4 h	19.6 mg/l (rat)

CAS: 140-31-8 2-piperazin-1-ylethylamine

Oral	LD50	2000-5000 mg/kg (rat) 500 mg/kg (rabbit)
	LD50	200-1000 mg/kg (rabbit)

CAS: 9046-10-0 Polyoxypropylenediamine

Oral	LD50	2855 mg/kg (Rat)
Dermal	LD50	2980 mg/kg (Kan)

CAS: 8028-48-6 Orange juice oil

Oral	LD50	>4400 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

CAS: 140-31-8 Aminoethylpiperazine

Oral	LD50	2000-5000 mg/kg (rat) 500 mg/kg (rabbit)
	LD50	200-1000 mg/kg (rabbit)

· **Primary irritant effect:**

· **Skin corrosion/irritation**

Caustic effect on skin and mucous membranes.

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 9)

· **Serious eye damage/irritation** Strong caustic effect.

· **Respiratory or skin sensitisation**

Sensitization possible by skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Repr. 2

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

CAS: 100-51-6 Benzyl alcohol

IC50/72h 700 mg/l (algae)

LC50/96h 460 mg/l (*Pimephales promelas*)

10 mg/l (*Lepomis macrochirus*)

CAS: 2855-13-2 Isophorone diamine

LC50/96h 110 mg/l (*Leucidus idus*)

EC50 1120 mg/l (*Pseudomonas putida*)

EC50/48h 23 mg/l (*Daphnia magna*)

NOEC 1.5 mg/l (*Desmodesmus subspicatus*)

3 mg/l (*Daphnia magna*)

ErC50/72h >50 mg/l (*Desmodesmus subspicatus*)

CAS: 15520-10-2 2-methylpentane-1,5-diamine

EC50/72h >100 mg/l (algae)

EC50 1825 mg/l (fish)

EC50/48h 19.8 mg/l (*Daphnia magna*)

CAS: 140-31-8 2-piperazin-1-ylethylamine

EC50/72h >1000 mg/l (algae)

LC50/96h 2190 mg/l (fish)

CAS: 140-31-8 Aminoethylpiperazine

EC50/72h >1000 mg/l (algae)

LC50/96h 2190 mg/l (fish)

· **Persistence and degradability** No further relevant information available.

(Contd. on page 11)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 10)

- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
 Must not reach sewage water or drainage ditch undiluted or unneutralised.
 Do not allow product to reach ground water, water bodies or sewage system.
 Danger to drinking water if even small quantities leak into soil.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|-------------------------------------|---|
| · UN-Number | |
| · ADR, IMDG, IATA | UN2735 |
| · UN proper shipping name | |
| · ADR, IMDG, IATA | AMINES, LIQUID, CORROSIVE, N.O.S.
(ISOPHORONEDIAMINE, 2-methylpentane-1,5-diamine) |
| · Transport hazard class(es) | |
| · ADR | |
| · Class | 8 (C7) Corrosive substances. |
| · Label | 8 |
| · IMDG, IATA | |
| · Class | 8 Corrosive substances. |
| · Label | 8 |
| · Packing group | |
| · ADR, IMDG, IATA | II |

(Contd. on page 12)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 11)

· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances.
· Kemler Number:	80
· EMS Number:	F-A,S-B
· Segregation groups	(SGG18) Alkalis
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· Transport in bulk according to Annex II of Marpol and the IBC Code	
Not applicable.	
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE, 2-METHYLPENTANE-1,5-DIAMINE), 8, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing data specification sheet:** Environment protection department.

(Contd. on page 13)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 23.03.2024

Version number 28

Revision: 23.03.2024

Trade name MC-Floor Connect Adhesive - Komponente B

(Contd. of page 12)

· **Contact:**

· **Abbreviations and acronyms:** RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Flam. Liq. 4: Flammable liquids – Category 4
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 5: Acute toxicity – Category 5
 Acute Tox. 3: Acute toxicity – Category 3
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1B: Skin sensitisation – Category 1B
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**