



BE SURE. BUILD SURE.

Page 1/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2025

Version number 28

Revision: 15.03.2025

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name** ombran FG plus
- **Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- **Application of the substance / the mixture** Filling mortar
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533
- **Informing department:** msds@mc-bauchemie.de

2 Hazards identification

- **Classification of the substance or mixture**
Skin Irrit. 2 H315 Causes skin irritation.
Eye Dam. 1 H318 Causes serious eye damage.
STOT SE 3 H335 May cause respiratory irritation.
- **Label elements**
- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**

GHS05 GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:** Portland cement (low chromate)
Flue dust, portland cement
calcium oxide
- **Hazard statements** H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

(Contd. on page 2)

AE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2025

Version number 28

Revision: 15.03.2025

Trade name ombran FG plus

- (Contd. of page 1)
- **Precautionary statements**
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P310 Immediately call a POISON CENTER/doctor.
 - P321 Specific treatment (see on this label).
 - P362+P364 Take off contaminated clothing and wash it before reuse.
 - P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 - **Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 65997-15-1	Portland cement (low chromate) Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	30-60%
CAS: 14808-60-7	Quartz sand	30-60%
CAS: 1317-65-3	Calcium carbonate Acute Tox. 5, H303; Acute Tox. 5, H313	<10%
CAS: 68475-76-3	Flue dust, portland cement Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥1-<3%
CAS: 1305-78-8	calcium oxide Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335; Acute Tox. 5, H303; Acute Tox. 5, H313	≥1-<2.5%
CAS: 21645-51-2	aluminium hydroxide Acute Tox. 5, H303	<2.5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **General information** For all first aid measures: observe self-protection and consult a doctor!
- **After inhalation** Remove people from the dusty area.
- **After skin contact** Remove heavily soiled clothing. Clean with plenty of soap and water.
- **After eye contact** Rinse for 10 minutes under running water with the eyelids open. Always consult an ophthalmologist!

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2025

Version number 28

Revision: 15.03.2025

Trade name ombran FG plus

· **After swallowing**

Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

(Contd. of page 2)

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:** Collect mechanically.
- **Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

7 Handling and storage

- **Handling**
- **Precautions for safe handling** Avoid dust formation! Avoid spraying the ready-to-use cementitious product! Avoid contact with eyes and skin! Clean hands thoroughly at the end of work and before every break! Use skin care products! Change heavily soiled clothing! Change clothes at the end of work! Apply greasy skin protection ointment before starting work and after each break. Observe work restrictions!
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Store bags tightly closed; protect from moisture and water!
Store containers tightly closed in a well-ventilated and well-lit room.
Access only for specialised personnel.
Do not store in break rooms, recreation rooms or sanitary facilities or in stairwells, corridors, escape and rescue routes, passages, passageways and confined spaces.
- **Information about storage in one common storage facility:** Combined storage bans apply from a total storage quantity of 200 kg.
Do not store together with substances of the following LGK: 1; 6.2; 7

(Contd. on page 4)

AE

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2025

Version number 28

Revision: 15.03.2025

Trade name ombran FG plus

(Contd. of page 3)

Storage with substances of the following LGK is only possible under the conditions specified in TRGS 510: 4.1A; 5.1C

- **Further information about storage conditions:**
- **Storage class**

Store in a dry and frost-free place.
13

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· **Components with critical values that require monitoring at the workplace:**

CAS: 65997-15-1 Portland cement (low chromate)

PEL (USA)	Long-term value: 50 mppcf or 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 1* mg/m ³ E; *as respirable fraction, A4
WEL (Great Britain)	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust

CAS: 14808-60-7 Quartz sand

PEL (USA)	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL (USA)	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV (USA)	Long-term value: 0.025* mg/m ³ *respirable particulate matter, A2
BOELV (European Union)	Long-term value: 0.1* mg/m ³ *respirable fraction

CAS: 1317-65-3 Calcium carbonate

WEL (Great Britain)	Long-term value: 10* 4** mg/m ³ *inhalable dust; **respirable
---------------------	---

CAS: 69012-64-2 amorphous silica (fume)

TLV (USA)	TLV withdrawn
-----------	---------------

CAS: 1305-78-8 calcium oxide

PEL (USA)	Long-term value: 5 mg/m ³
REL (USA)	Long-term value: 2 mg/m ³
TLV (USA)	Long-term value: 2 mg/m ³
IOELV (European Union)	Short-term value: 4 mg/m ³ Long-term value: 1 mg/m ³ Respirable fraction

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2025

Version number 28

Revision: 15.03.2025

Trade name ombran FG plus

(Contd. of page 4)

WEL (Great Britain)	Short-term value: 4* mg/m ³ Long-term value: 2 1* mg/m ³ *respirable fraction
CAS: 21645-51-2 aluminium hydroxide	
REL (USA)	Long-term value: 2 mg/m ³ as Al
WEL (Great Britain)	Long-term value: 2 mg/m ³
· DNELs	
CAS: 65997-15-1 Portland cement (low chromate)	
Inhalative DNEL	1 mg/m ³ (ArL)
CAS: 1317-65-3 Calcium carbonate	
Oral DNEL	6.1 mg/kg bw/Tag (ArL)
Inhalative DNEL	10 mg/m ³ (ArL)
CAS: 1305-78-8 calcium oxide	
Inhalative DNEL	1 mg/m ³ (ArL)
CAS: 21645-51-2 aluminium hydroxide	
Oral DNEL	6.89 mg/kg bw/Tag (ArL)
Inhalative DNEL	3.59 mg/m ³ (ArL)
· PNECs	
CAS: 1317-65-3 Calcium carbonate	
PNEC	100 mg/l (Sewage Treatment Plant)
CAS: 1305-78-8 calcium oxide	
PNEC	2.27 mg/l (BEL) 0.24 mg/l (Mew) 0.37 mg/l (Freshwater)
PNEC	817.4 mg/kg dwt (Bod)
CAS: 21645-51-2 aluminium hydroxide	
PNEC	20 mg/l (Kla)

· Additional information: The lists that were valid during the compilation were used as basis.

- **Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**

Do not store food, eat, drink, sniff or smoke in the work area!
Avoid contact with eyes and skin!
Clean hands thoroughly at the end of work and before breaks!
Use skin care products after work (moisturising cream).
Change and clean heavily soiled clothing!
Change clothes at the end of work!
Apply greasy skin protection ointment before starting work and after every break.

- **Breathing equipment:** For work with higher dust loads particle filter class P2
- **Protection of hands:** Check protective gloves prior to each use for their proper condition.

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2025

Version number 28

Revision: 15.03.2025

Trade name ombran FG plus

(Contd. of page 5)

- **Material of gloves** Nitrile impregnated cotton gloves.
- **Penetration time of glove material** The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.
- **Eye protection:** Safety glasses
- **Body protection:** Protective work clothing.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

- Form: Powder
- Colour: Grey
- Smell: Odourless

- **pH-value:** Not applicable.

· Change in condition

- Melting point/freezing point: Not determined
- Initial boiling point and boiling range: 2230 °C

- **Flash point:** Not applicable

- **Self-inflammability:** Product is not selfigniting.

- **Explosive properties:** Product is not explosive.

- **Steam pressure at 1732 °C:** 13.5 hPa

- **Density** Not determined

- **Solubility in / Miscibility with Water:**

Unsoluble

· Viscosity:

- dynamic: Not applicable.
- kinematic: Not applicable.

- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· Possibility of hazardous reactions

No dangerous reactions known

· Conditions to avoid

No further relevant information available.

· Incompatible materials:

No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2025

Version number 28

Revision: 15.03.2025

Trade name ombran FG plus

(Contd. of page 6)

· **Hazardous decomposition products:**

No dangerous decomposition products known

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity**

· **LD/LC50 values that are relevant for classification:**

CAS: 65997-15-1 Portland cement (low chromate)

Dermal LD50 2000 mg/kg (rabbit)

Inhalative LC50/4 h 5 mg/l (rat)

CAS: 1317-65-3 Calcium carbonate

Oral LD50 >2000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rat)

CAS: 1305-78-8 calcium oxide

Oral LD50 >2000 mg/kg (rat)

Dermal LD50 >2500 mg/kg (rabbit)

CAS: 21645-51-2 aluminium hydroxide

Oral LD50 >2000 mg/kg (rat)

· **Primary irritant effect:**

· **Skin corrosion/irritation** Irritant for skin and mucous membranes.

· **Serious eye damage/irritation** Strong irritant with the danger of severe eye injury.

· **Respiratory or skin sensitisation** No sensitizing effect known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

CAS: 1317-65-3 Calcium carbonate

EC50/72h >14 mg/l (Desmodesmus subspicatus)

LC50/96h >10000 mg/l (Oncorhynchus mykiss)

LC50/48h >1000 mg/l (Daphnia magna)

EC50/48h >1000 mg/l (Daphnia magna)

CAS: 1305-78-8 calcium oxide

EC50/72h 184.57 mg/l (algae)

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2025

Version number 28

Revision: 15.03.2025

Trade name ombran FG plus

(Contd. of page 7)

LC50/96h	50.6 mg/l (Fis) 158 mg/l (Mew)
EC50/48h	49.1 mg/l (Freshwater)
NOEC	32 mg/l (Mew) 48 mg/l (algae)
CAS: 21645-51-2 aluminium hydroxide	
NOEC	0.004 mg/l (Freshwater) >0.005 mg/l (Daphnia magna) >0.07 mg/l (fish)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	
· ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· ADR, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· ADR, IMDG, IATA	Void

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 15.03.2025

Version number 28

Revision: 15.03.2025

Trade name ombran FG plus

(Contd. of page 8)

- | | |
|---|-----------------|
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** *None of the ingredients is listed.*
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

- **Department issuing data specification sheet:** *Environment protection department.*
- **Contact:**
- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 5: Acute toxicity – Category 5

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- *** Data compared to the previous version altered.**